

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P203476

Luminaire Tested: **LSR6B40D010BZ EC6B30509040 6LBMB1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P203476
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LSR6B40D010BZ EC6B30509040 6LBMB1
Description: PORTFOLIO 6IN CYLINDER
MEDIUM DISTRIBUTION WITH SPECULAR BLACK TRIM
WATTAGE D010TR-43.02 W DE010-42.54 W D5LT-42.539 W DMX-41.87 W DL2-41.57
W DL3-44.71 W DLE-39.33 W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1578.2 lumens
Efficiency: N/A
Efficacy: 37.8 lumens/watt
Spacing Criteria (0/90/45): 0.85 / 0.85 / 0.86
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 41.8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P203476

CATALOG NUMBER: LSR6B40D010BZ EC6B30509040 6LBMB1

Luminous Intensity Polar Plot





TEST NUMBER: P203476

CATALOG NUMBER: LSR6B40D010BZ EC6B30509040 6LBMB1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									20																	
RC	80									70									50									30									10									0								
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10																						
RCR	0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	100	100	100	100	100	100	100	100	100	100	100	100																							
	1	114	111	109	106	111	109	107	105	105	103	102	101	100	99	98	97	96	94	94	94	94	94	94	94	94	94	94	94	94	94																							
	2	108	104	100	96	106	102	98	95	99	96	93	96	93	91	93	91	89	88	88	88	88	88	88	88	88	88	88	88	88	88																							
	3	103	97	92	88	101	95	91	87	93	89	86	90	87	85	88	86	83	82	82	82	82	82	82	82	82	82	82	82	82	82																							
	4	98	91	85	81	96	90	85	81	87	83	80	85	82	79	84	81	78	76	76	76	76	76	76	76	76	76	76	76	76	76																							
	5	93	85	79	75	92	84	79	75	82	78	74	81	77	74	79	76	73	72	72	72	72	72	72	72	72	72	72	72	72	72																							
	6	89	80	74	70	87	79	74	70	78	73	69	76	72	69	75	71	68	67	67	67	67	67	67	67	67	67	67	67	67	67																							
	7	84	75	69	65	83	75	69	65	73	68	65	72	68	65	71	67	64	63	63	63	63	63	63	63	63	63	63	63	63	63																							
	8	80	71	65	61	79	71	65	61	69	64	61	68	64	61	67	63	60	59	59	59	59	59	59	59	59	59	59	59	59	59																							
	9	77	67	61	58	76	67	61	57	66	61	57	65	60	57	64	60	57	56	56	56	56	56	56	56	56	56	56	56	56	56																							
	10	73	64	58	54	72	63	58	54	62	57	54	62	57	54	61	57	54	53	53	53	53	53	53	53	53	53	53	53	53	53																							

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P203476

CATALOG NUMBER: LSR6B40D010BZ EC6B30509040 6LBMB1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	180.2	11.4
10°-20°	444.8	28.2
20°-30°	535.8	33.9
30°-40°	338.9	21.5
40°-50°	77.6	4.9
50°-60°	0.9	0.1
60°-70°	0.0	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1160.9	73.6
0°-40°	1499.8	95.0
0°-60°	1578.2	100.0
0°-90°	1578.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1578.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1987	
5°	1942	180
15°	1587	445
25°	1187	536
35°	534	339
45°	86	78
55°	0	1
65°	0	0
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P203476

CATALOG NUMBER: LSR6B40D010BZ EC6B30509040 6LBMB1

CANDELA DISTRIBUTION (FULL):

0°	
0°	1986.8
2.5°	1978.7
5°	1942.0
7.5°	1872.6
10°	1786.9
12.5°	1684.9
15°	1587.0
17.5°	1493.2
20°	1395.3
22.5°	1297.4
25°	1187.2
27.5°	1056.7
30°	897.5
32.5°	718.0
35°	534.4
37.5°	379.4
40°	257.0
42.5°	159.1
45°	85.7
47.5°	36.7
50°	8.2
52.5°	0.0
55°	0.0
57.5°	0.0
60°	0.0
62.5°	0.0
65°	0.0
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)