

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P203373

Luminaire Tested: **LSR6B40D010BZ EC6B30509040 6LBMWH1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P203373
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LSR6B40D010BZ EC6B30509040 6LBMWH1
Description: PORTFOLIO 6IN CYLINDER
MEDIUM DISTRIBUTION WITH WHEAT TRIM
WATTAGE D010TR-43.02 W DE010-42.54 W D5LT-42.539 W DMX-41.87 W DL2-41.57
W DL3-44.71 W DLE-39.33 W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2861.6 lumens
Efficiency: N/A
Efficacy: 68.5 lumens/watt
Spacing Criteria (0/90/45): 0.83 / 0.83 / 0.85
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 41.8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P203373

CATALOG NUMBER: LSR6B40D010BZ EC6B30509040 6LBMWH1

Luminous Intensity Polar Plot





TEST NUMBER: P203373

CATALOG NUMBER: LSR6B40D010BZ EC6B30509040 6LBMWH1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	114	111	108	106	111	109	106	104	105	103	101	101	100	98	97	96	95	94																			
2	108	103	99	96	106	101	98	95	98	95	93	95	93	91	92	91	89	87																			
3	103	96	91	87	101	95	90	87	92	88	85	90	87	84	88	85	83	81																			
4	97	90	85	80	96	89	84	80	87	82	79	85	81	78	83	80	77	76																			
5	93	84	79	74	91	83	78	74	82	77	73	80	76	73	78	75	72	71																			
6	88	79	73	69	87	78	73	69	77	72	68	76	71	68	74	70	67	66																			
7	84	75	69	64	82	74	68	64	73	68	64	71	67	64	70	66	63	62																			
8	80	70	64	60	78	70	64	60	69	64	60	68	63	60	67	62	59	58																			
9	76	66	61	57	75	66	60	57	65	60	56	64	59	56	63	59	56	55																			
10	72	63	57	53	71	62	57	53	62	57	53	61	56	53	60	56	53	52																			

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P203373

CATALOG NUMBER: LSR6B40D010BZ EC6B30509040 6LBMWH1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	326.3	11.4
10°-20°	801.2	28.0
20°-30°	927.0	32.4
30°-40°	592.6	20.7
40°-50°	168.0	5.9
50°-60°	30.0	1.0
60°-70°	12.3	0.4
70°-80°	4.2	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2054.6	71.8
0°-40°	2647.1	92.5
0°-60°	2845.1	99.4
0°-90°	2861.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2861.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3570	
5°	3506	326
15°	2873	801
25°	2046	927
35°	935	593
45°	195	168
55°	28	30
65°	12	12
75°	4	4
85°	0	0
90°	0	



TEST NUMBER: P203373

CATALOG NUMBER: LSR6B40D010BZ EC6B30509040 6LBMWH1

CANDELA DISTRIBUTION (FULL):

	0°
0°	3569.8
2.5°	3565.8
5°	3506.1
7.5°	3398.7
10°	3247.5
12.5°	3072.4
15°	2873.4
17.5°	2666.4
20°	2463.5
22.5°	2264.5
25°	2045.6
27.5°	1806.8
30°	1540.2
32.5°	1241.7
35°	935.2
37.5°	676.6
40°	469.6
42.5°	310.4
45°	195.0
47.5°	115.4
50°	67.7
52.5°	39.8
55°	27.9
57.5°	23.9
60°	19.9
62.5°	15.9
65°	11.9
67.5°	8.0
70°	8.0
72.5°	4.0
75°	4.0
77.5°	4.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)