

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P179710

Luminaire Tested: **LDA6A65835D010TE LARH30NF 6LA1LI**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P179710
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P26623)
Test Lab: INNOVATION CENTER-P2
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LDA6A65835D010TE LARH30NF 6LA1LI
Description: PORTFOLIO 6" Adjustable Reflector, Angle-cut Trim, Self-flanged, 30°
Narrow Flood
Light Source: (1) HIGH LUMEN LED 80CRI / 3500K CCT
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 6580.0 lumens
Efficiency: N/A
Efficacy: 84.4 lumens/watt
Spacing Criteria (0/90/45): 0.57 / 0.57 / 0.55
Luminous Opening: Circular (Dia: 0.5' x H: 0')
CIE Type: Direct


Input Watts (W): 78
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P179710

CATALOG NUMBER: LDA6A65835D010TE LARH30NF 6LA1LI

Luminous Intensity Polar Plot





TEST NUMBER: P179710

CATALOG NUMBER: LDA6A65835D010TE LARH30NF 6LA1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20																		
RC	80									70									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR	0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	100	100	100	100	100	100	100	100	100	100	100																
	1	115	113	111	109	112	110	109	107	106	105	104	103	102	101	99	99	98	96	96	96	96	96	96	96	96	96	96	96	96																
	2	111	107	104	101	109	105	103	100	102	100	98	99	98	96	97	95	94	92	92	92	92	92	92	92	92	92	92	92	92																
	3	107	102	98	95	105	101	97	95	98	95	93	96	94	92	94	92	90	89	89	89	89	89	89	89	89	89	89	89	89																
	4	103	98	94	90	102	97	93	90	95	91	89	93	90	88	91	89	87	86	86	86	86	86	86	86	86	86	86	86	86																
	5	100	94	89	86	99	93	89	86	91	88	85	90	87	84	88	86	84	83	83	83	83	83	83	83	83	83	83	83	83																
	6	97	90	86	82	95	89	85	82	88	84	82	87	84	81	86	83	81	80	80	80	80	80	80	80	80	80	80	80	80																
	7	94	87	82	79	93	86	82	79	85	81	79	84	81	78	83	80	78	77	77	77	77	77	77	77	77	77	77	77	77																
	8	91	84	79	76	90	83	79	76	82	78	76	81	78	75	80	77	75	74	74	74	74	74	74	74	74	74	74	74	74																
	9	88	81	76	73	87	80	76	73	80	76	73	79	75	73	78	75	73	72	72	72	72	72	72	72	72	72	72	72	72																
	10	85	78	74	71	84	78	74	71	77	73	71	76	73	70	76	73	70	69	69	69	69	69	69	69	69	69	69	69	69																

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	1063961
5°	985492
10°	877929
15°	669930
20°	401637
25°	221354
30°	54762
35°	4230
40°	1195
45°	465
50°	205
55°	229
60°	263
65°	156
70°	192
75°	254
80°	379
85°	0



TEST NUMBER: P179710

CATALOG NUMBER: LDA6A65835D010TE LARH30NF 6LA1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	1647.6	25.0
10°-20°	3158.5	48.0
20°-30°	1631.2	24.8
30°-40°	132.2	2.0
40°-50°	5.4	0.1
50°-60°	2.2	0.0
60°-70°	1.6	0.0
70°-80°	1.3	0.0
80°-90°	0.2	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	6437.2	97.8
0°-40°	6569.4	99.8
0°-60°	6577.0	100.0
0°-90°	6580.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6580.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	19408	
5°	17908	###
15°	11804	3159
25°	3660	1631
35°	63	132
45°	6	5
55°	2	2
65°	1	2
75°	1	1
85°	0	0
90°	0	



TEST NUMBER: P179710

CATALOG NUMBER: LDA6A65835D010TE LARH30NF 6LA1LI

CANDELA DISTRIBUTION (FULL):

	0°
0°	19408.2
2.5°	18965.5
5°	17908.4
7.5°	16945.5
10°	15771.4
12.5°	14192.8
15°	11804.1
17.5°	9151.7
20°	6884.6
22.5°	5047.1
25°	3659.5
27.5°	2203.8
30°	865.1
32.5°	367.5
35°	63.2
37.5°	31.0
40°	16.7
42.5°	9.5
45°	6.0
47.5°	3.6
50°	2.4
52.5°	2.4
55°	2.4
57.5°	2.4
60°	2.4
62.5°	2.4
65°	1.2
67.5°	1.2
70°	1.2
72.5°	1.2
75°	1.2
77.5°	1.2
80°	1.2
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)