

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P179823

Luminaire Tested: **LDA6A65840D010TE LARH40FL 6LFC1H**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P179823
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P26683)
Test Lab: INNOVATION CENTER-P2
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LDA6A65840D010TE LARH40FL 6LFC1H
Description: PORTFOLIO 6" Flat Cone, Self-flanged, 40° Flood
Light Source: (1) HIGH LUMEN LED 80CRI / 4000K CCT
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 6913.4 lumens
Efficiency: N/A
Efficacy: 88.6 lumens/watt
Spacing Criteria (0/90/45): 0.67 / 0.67 / 0.61
Luminous Opening: Circular (Dia: 0.5' x H: 0')
CIE Type: Direct


Input Watts (W): 78
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P179823

CATALOG NUMBER: LDA6A65840D010TE LARH40FL 6LFC1H

Luminous Intensity Polar Plot





TEST NUMBER: P179823

CATALOG NUMBER: LDA6A65840D010TE LARH40FL 6LFC1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			100
1	115	112	110	108	112	110	108	107	106	105	104	103	101	100	99	98	98	96			96
2	110	107	103	101	108	105	102	99	102	99	97	99	97	95	96	95	93	92			92
3	106	101	97	94	105	100	97	94	98	95	92	95	93	91	93	91	89	88			88
4	103	97	92	89	101	96	92	89	94	90	88	92	89	87	90	88	86	84			84
5	99	93	88	85	98	92	88	84	90	86	84	89	85	83	87	84	82	81			81
6	96	89	84	81	94	88	84	81	87	83	80	85	82	80	84	81	79	78			78
7	92	85	81	77	91	85	80	77	83	80	77	82	79	76	81	78	76	75			75
8	89	82	77	74	88	81	77	74	80	77	74	80	76	73	79	76	73	72			72
9	86	79	74	71	85	78	74	71	78	74	71	77	73	71	76	73	70	69			69
10	84	76	72	69	83	76	71	68	75	71	68	74	71	68	74	70	68	67			67

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	943488
5°	851880
10°	775231
15°	708653
20°	517199
25°	254718
30°	55192
35°	10487
40°	2805
45°	1233
50°	733
55°	583
60°	537
65°	480
70°	385
75°	254
80°	0
85°	0



TEST NUMBER: P179823

CATALOG NUMBER: LDA6A65840D010TE LARH40FL 6LFC1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	1431.8	20.7
10°-20°	3354.2	48.5
20°-30°	1934.9	28.0
30°-40°	168.3	2.4
40°-50°	14.0	0.2
50°-60°	5.6	0.1
60°-70°	3.3	0.0
70°-80°	1.3	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	6720.9	97.2
0°-40°	6889.2	99.7
0°-60°	6908.8	99.9
0°-90°	6913.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6913.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	17211	
5°	15480	###
15°	12486	3354
25°	4211	1935
35°	157	168
45°	16	14
55°	6	6
65°	4	3
75°	1	1
85°	0	0
90°	0	



TEST NUMBER: P179823

CATALOG NUMBER: LDA6A65840D010TE LARH40FL 6LFC1H

CANDELA DISTRIBUTION (FULL):

	0°
0°	17210.6
2.5°	16347.3
5°	15480.4
7.5°	14669.7
10°	13926.5
12.5°	13286.0
15°	12486.4
17.5°	11130.9
20°	8865.5
22.5°	6417.7
25°	4211.1
27.5°	2182.1
30°	871.9
32.5°	458.0
35°	156.7
37.5°	64.9
40°	39.2
42.5°	24.5
45°	15.9
47.5°	9.8
50°	8.6
52.5°	7.3
55°	6.1
57.5°	4.9
60°	4.9
62.5°	3.7
65°	3.7
67.5°	2.4
70°	2.4
72.5°	1.2
75°	1.2
77.5°	1.2
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)