

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P203525

Luminaire Tested: **LE_6B10D010 EC6B10209030 6LBMMW1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P203525
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LE_6B10D010 EC6B10209030 6LBMMW1
Description: PORTFOLIO 6 INCH 50 DEGREE CUTOFF RECESSED DOWNLIGHT
MEDIUM DISTRIBUTION WITH MATTE WHITE TRIM
WATTAGE D010TR-10.05 W DE010-10.58 W D5LT-10.2 W DMX-10.6 W DL2-11.8 W
DL3-11.1 W DLE-11.39 W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 910.0 lumens
Efficiency: N/A
Efficacy: 91.9 lumens/watt
Spacing Criteria (0/90/45): 1 / 1 / 0.97
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct

Input Watts (W): 9.9
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P203525
CATALOG NUMBER: LE_6B10D010 EC6B10209030 6LBMMW1

Luminous Intensity Polar Plot





TEST NUMBER: P203525

CATALOG NUMBER: LE_6B10D010 EC6B10209030 6LBMMW1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10			
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	111	108	104	101	109	105	103	100	101	99	97	98	96	94	94	92	91	89		
2	104	97	92	88	101	96	91	87	92	88	85	89	86	83	86	83	81	79		
3	97	88	82	77	95	87	81	76	84	79	75	82	77	74	79	76	73	71		
4	90	81	74	68	88	80	73	68	77	72	67	75	70	66	73	69	65	64		
5	85	74	67	61	83	73	66	61	71	65	61	69	64	60	68	63	59	58		
6	79	68	61	56	78	68	61	56	66	60	55	64	59	55	63	58	54	53		
7	75	63	56	51	73	63	56	51	61	55	50	60	54	50	59	54	50	48		
8	70	59	52	47	69	58	51	47	57	51	46	56	50	46	55	50	46	44		
9	66	55	48	43	65	54	48	43	53	47	43	52	47	43	51	46	43	41		
10	63	51	45	40	62	51	44	40	50	44	40	49	44	40	48	43	40	38		

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P203525

CATALOG NUMBER: LE_6B10D010 EC6B10209030 6LBMMW1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	62.7	6.9
10°-20°	168.0	18.5
20°-30°	225.6	24.8
30°-40°	185.1	20.3
40°-50°	111.1	12.2
50°-60°	73.8	8.1
60°-70°	49.5	5.4
70°-80°	26.6	2.9
80°-90°	7.5	0.8
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	456.4	50.1
0°-40°	641.5	70.5
0°-60°	826.4	90.8
0°-90°	910.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	910.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	679	
5°	668	63
15°	599	168
25°	497	226
35°	294	185
45°	141	111
55°	82	74
65°	50	49
75°	25	27
85°	6	7
90°	0	



TEST NUMBER: P203525

CATALOG NUMBER: LE_6B10D010 EC6B10209030 6LBMMW1

CANDELA DISTRIBUTION (FULL):

	0°
0°	679.1
2.5°	674.0
5°	667.8
7.5°	654.0
10°	637.6
12.5°	617.6
15°	598.8
17.5°	576.1
20°	553.5
22.5°	528.5
25°	497.1
27.5°	459.4
30°	409.2
32.5°	352.8
35°	293.8
37.5°	243.5
40°	200.9
42.5°	167.0
45°	140.6
47.5°	119.2
50°	104.1
52.5°	91.6
55°	81.6
57.5°	72.8
60°	65.2
62.5°	56.5
65°	50.2
67.5°	42.6
70°	36.4
72.5°	30.1
75°	25.1
77.5°	20.1
80°	15.1
82.5°	11.2
85°	6.2
87.5°	2.5
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)