

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P203538

Luminaire Tested: **LE_6B15D010 EC6B10209030 6LBMMW1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P203538
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LE_6B15D010 EC6B10209030 6LBMMW1
Description: PORTFOLIO 6 INCH 50 DEGREE CUTOFF RECESSED DOWNLIGHT
MEDIUM DISTRIBUTION WITH MATTE WHITE TRIM
WATTAGE D010TR-14.39 W DE010-14.29 W D5LT-14.34 W DMX-14.46 W DL2-15.8 W
DL3-15.28 W DLE-15.432 W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1255.6 lumens
Efficiency: N/A
Efficacy: 87.8 lumens/watt
Spacing Criteria (0/90/45): 1 / 1 / 0.97
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 14.3
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P203538

CATALOG NUMBER: LE_6B15D010 EC6B10209030 6LBMMW1

Luminous Intensity Polar Plot





TEST NUMBER: P203538

CATALOG NUMBER: LE_6B15D010 EC6B10209030 6LBMMW1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	111	108	104	101	109	105	103	100	101	99	97	98	96	94	94	92	91	89
2	104	97	92	88	101	96	91	87	92	88	85	89	86	83	86	83	81	79
3	97	88	82	77	95	87	81	76	84	79	75	82	77	74	79	76	73	71
4	90	81	74	68	88	80	73	68	77	72	67	75	70	66	73	69	65	64
5	85	74	67	61	83	73	66	61	71	65	61	69	64	60	68	63	59	58
6	79	68	61	56	78	68	61	56	66	60	55	64	59	55	63	58	54	53
7	75	63	56	51	73	63	56	51	61	55	50	60	54	50	59	54	50	48
8	70	59	52	47	69	58	51	47	57	51	46	56	50	46	55	50	46	44
9	66	55	48	43	65	54	48	43	53	47	43	52	47	43	51	46	43	41
10	63	51	45	40	62	51	44	40	50	44	40	49	44	40	48	43	40	38

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P203538

CATALOG NUMBER: LE_6B15D010 EC6B10209030 6LBMMW1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	86.5	6.9
10°-20°	231.8	18.5
20°-30°	311.3	24.8
30°-40°	255.3	20.3
40°-50°	153.4	12.2
50°-60°	101.9	8.1
60°-70°	68.3	5.4
70°-80°	36.8	2.9
80°-90°	10.4	0.8
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	629.6	50.1
0°-40°	885.0	70.5
0°-60°	1140.2	90.8
0°-90°	1255.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1255.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	937	
5°	921	87
15°	826	232
25°	686	311
35°	405	255
45°	194	153
55°	113	102
65°	69	68
75°	35	37
85°	9	10
90°	0	



TEST NUMBER: P203538

CATALOG NUMBER: LE_6B15D010 EC6B10209030 6LBMMW1

CANDELA DISTRIBUTION (FULL):

	0°
0°	936.9
2.5°	930.0
5°	921.2
7.5°	902.2
10°	879.8
12.5°	852.0
15°	826.0
17.5°	794.9
20°	763.8
22.5°	729.1
25°	685.8
27.5°	633.9
30°	564.5
32.5°	486.6
35°	405.2
37.5°	336.0
40°	277.1
42.5°	230.4
45°	194.0
47.5°	164.5
50°	143.8
52.5°	126.4
55°	112.6
57.5°	100.5
60°	90.0
62.5°	77.9
65°	69.2
67.5°	58.9
70°	50.2
72.5°	41.5
75°	34.6
77.5°	27.8
80°	20.8
82.5°	15.6
85°	8.6
87.5°	3.5
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)