

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P202828

Luminaire Tested: **LE\_6B20D010 EC6B10209024 6LBWWH1**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-41-14  
Report Number: P202828  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)  
Test Lab: INNOVATION CENTER-P3  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: PORTFOLIO  
Catalog Number: LE\_6B20D010 EC6B10209024 6LBWWH1  
Description: PORTFOLIO 6 INCH 60 DEGREE CUTOFF RECESSED DOWNLIGHT  
WIDE DISTRIBUTION WITH WHEAT TRIM  
WATTAGE D010TR-21.86 W DE010-20.46 W D5LT-21.24 W DMX-20.89 W DL2-22.5 W  
DL3-21.8 6 W DLE-22.46 W  
Light Source: HIGH LUMEN LED  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 1682.9 lumens  
Efficiency: N/A  
Efficacy: 80.9 lumens/watt  
Spacing Criteria (0/90/45): 1.23 / 1.23 / 1.18  
Luminous Opening: Point Source (0' x 0' x 0')  
CIE Type: Direct


Input Watts (W): 20.8  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P202828

CATALOG NUMBER: LE\_6B20D010 EC6B10209024 6LBWWH1

### Luminous Intensity Polar Plot





TEST NUMBER: P202828

CATALOG NUMBER: LE\_6B20D010 EC6B10209024 6LBWWH1

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	113	109	107	104	110	107	105	102	103	101	99	99	98	96	96	95	93	92			
2	106	100	96	92	104	98	94	91	95	92	89	92	89	87	89	87	85	83			
3	99	92	86	81	97	90	85	81	88	83	79	85	81	78	83	80	77	75			
4	93	84	78	73	91	83	77	72	81	76	71	79	74	71	77	73	70	68			
5	87	77	71	66	85	76	70	65	75	69	65	73	68	64	71	67	63	62			
6	82	71	64	59	80	71	64	59	69	63	59	67	62	58	66	61	58	56			
7	77	66	59	54	75	65	59	54	64	58	54	63	57	53	61	57	53	51			
8	72	61	54	49	71	61	54	49	59	53	49	58	53	49	57	52	49	47			
9	68	57	50	45	67	56	50	45	55	49	45	54	49	45	53	48	45	43			
10	64	53	46	42	63	53	46	42	52	46	42	51	45	42	50	45	41	40			

**AVERAGE LUMINANCE (cd/sqm):**





TEST NUMBER: P202828

CATALOG NUMBER: LE\_6B20D010 EC6B10209024 6LBWWH1

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	100.5	6.0
10°-20°	298.8	17.8
20°-30°	449.7	26.7
30°-40°	459.8	27.3
40°-50°	279.3	16.6
50°-60°	78.7	4.7
60°-70°	12.0	0.7
70°-80°	3.9	0.2
80°-90°	0.3	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	849.0	50.4
0°-40°	1308.8	77.8
0°-60°	1666.7	99.0
0°-90°	1682.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1682.9	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	1045	
5°	1049	100
15°	1058	299
25°	982	450
35°	745	460
45°	359	279
55°	78	79
65°	10	12
75°	4	4
85°	0	0
90°	0	



TEST NUMBER: P202828

CATALOG NUMBER: LE\_6B20D010 EC6B10209024 6LBWWH1

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	1045.2
2.5°	1045.2
5°	1049.4
7.5°	1055.8
10°	1055.8
12.5°	1060.0
15°	1057.9
17.5°	1053.6
20°	1038.9
22.5°	1017.8
25°	981.9
27.5°	941.8
30°	886.9
32.5°	821.4
35°	745.4
37.5°	660.9
40°	563.8
42.5°	462.4
45°	359.0
47.5°	266.0
50°	187.9
52.5°	126.8
55°	78.1
57.5°	46.5
60°	23.2
62.5°	14.8
65°	10.5
67.5°	8.5
70°	6.4
72.5°	4.2
75°	4.2
77.5°	2.1
80°	2.1
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093







— 0°-180°







(END OF REPORT)