

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P202624

Luminaire Tested: **LE\_6B20D010 EC6B10209030 6LBMWMH1**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-41-14  
Report Number: P202624  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)  
Test Lab: INNOVATION CENTER-P3  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: PORTFOLIO  
Catalog Number: LE\_6B20D010 EC6B10209030 6LBMWMH1  
Description: PORTFOLIO 6 INCH 50 DEGREE CUTOFF RECESSED DOWNLIGHT  
MEDIUM DISTRIBUTION WITH WARM HAZE TRIM  
WATTAGE D010TR-21.86 W DE010-20.46 W D5LT-21.24 W DMX-20.89 W DL2-22.5 W  
DL3-21.8 6 W DLE-22.46 W  
Light Source: HIGH LUMEN LED  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 1707.2 lumens  
Efficiency: N/A  
Efficacy: 82.1 lumens/watt  
Spacing Criteria (0/90/45): 0.9 / 0.9 / 0.89  
Luminous Opening: Point Source (0' x 0' x 0')  
CIE Type: Direct


Input Watts (W): 20.8  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P202624

CATALOG NUMBER: LE\_6B20D010 EC6B10209030 6LBMWMH1

### Luminous Intensity Polar Plot





TEST NUMBER: P202624

CATALOG NUMBER: LE\_6B20D010 EC6B10209030 6LBMWMH1

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20									20									20									20									20																	
RC	80									70									50									30									10									0								
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																								
RCR																																																						
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																																				
1	113	111	108	106	111	108	106	104	104	103	101	101	99	98	97	96	95	93																																				
2	108	103	99	95	105	101	97	94	98	95	92	95	92	90	92	90	88	86																																				
3	102	95	90	86	100	94	89	86	91	88	84	89	86	83	87	84	82	80																																				
4	97	89	83	79	95	88	83	79	86	81	78	84	80	77	82	79	76	74																																				
5	92	83	77	73	90	82	77	73	80	76	72	79	75	71	77	74	71	69																																				
6	87	78	72	67	85	77	71	67	76	71	67	74	70	66	73	69	66	64																																				
7	83	73	67	63	81	72	67	63	71	66	62	70	65	62	69	65	61	60																																				
8	78	69	63	58	77	68	62	58	67	62	58	66	61	58	65	61	58	56																																				
9	75	65	59	55	73	64	59	55	63	58	54	62	58	54	62	57	54	53																																				
10	71	61	55	51	70	61	55	51	60	55	51	59	54	51	58	54	51	50																																				

**AVERAGE LUMINANCE (cd/sqm):**





TEST NUMBER: P202624

CATALOG NUMBER: LE\_6B20D010 EC6B10209030 6LBMWMH1

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	174.2	10.2
10°-20°	447.3	26.2
20°-30°	549.4	32.2
30°-40°	376.7	22.1
40°-50°	121.1	7.1
50°-60°	24.5	1.4
60°-70°	9.6	0.6
70°-80°	3.6	0.2
80°-90°	0.6	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1170.9	68.6
0°-40°	1547.6	90.7
0°-60°	1693.3	99.2
0°-90°	1707.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1707.2	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	1898	
5°	1862	174
15°	1600	447
25°	1212	549
35°	601	377
45°	143	121
55°	25	25
65°	10	10
75°	3	4
85°	0	1
90°	0	



TEST NUMBER: P202624

CATALOG NUMBER: LE\_6B20D010 EC6B10209030 6LBMWMH1

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	1898.5
2.5°	1886.9
5°	1862.2
7.5°	1815.9
10°	1753.6
12.5°	1676.9
15°	1600.1
17.5°	1514.8
20°	1420.6
22.5°	1322.1
25°	1212.1
27.5°	1090.4
30°	936.9
32.5°	767.5
35°	601.0
37.5°	448.9
40°	322.9
42.5°	220.1
45°	143.4
47.5°	88.4
50°	53.6
52.5°	33.2
55°	24.6
57.5°	18.9
60°	14.5
62.5°	11.6
65°	10.1
67.5°	7.2
70°	5.8
72.5°	4.4
75°	2.9
77.5°	2.9
80°	1.5
82.5°	1.5
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093







— 0°-180°







(END OF REPORT)