

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P204784

Luminaire Tested: **LE_6B20D010 EC6B10208035 6LBCSMW1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P204784
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LE_6B20D010 EC6B10208035 6LBCSMW1
Description: PORTFOLIO 6 INCH SHALLOW RECESSED DOWNLIGHT
SHALLOW DISTRIBUTION WITH CAST MATTE WHITE TRIM
WATTAGE D010TR-21.86 W DE010-20.46 W D5LT-21.24 W DMX-20.89 W DL2-22.5 W
DL3-21.8 6 W DLE-22.46 W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2867.4 lumens
Efficiency: N/A
Efficacy: 137.9 lumens/watt
Spacing Criteria (0/90/45): 1.23 / 1.23 / 1.33
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 20.8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P204784

CATALOG NUMBER: LE_6B20D010 EC6B10208035 6LBCSMW1

Luminous Intensity Polar Plot





TEST NUMBER: P204784

CATALOG NUMBER: LE_6B20D010 EC6B10208035 6LBCSMW1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				20	
RC	80				70				50				30				10				0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0	
RCR																						
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100				100
1	110	106	102	99	108	104	100	97	100	97	94	96	93	91	92	90	89	87				87
2	101	94	87	82	99	92	86	81	88	84	79	85	81	78	82	79	76	74				74
3	93	83	75	70	90	81	74	69	79	73	68	76	71	67	73	69	65	63				63
4	85	74	66	60	83	73	65	59	70	64	58	68	62	58	66	61	57	55				55
5	79	66	58	52	77	65	57	51	63	56	51	61	55	50	60	54	50	48				48
6	73	60	52	45	71	59	51	45	57	50	45	56	49	44	54	49	44	42				42
7	68	55	46	40	66	54	46	40	52	45	40	51	44	40	50	44	39	37				37
8	63	50	42	36	61	49	41	36	48	41	36	47	40	36	46	40	35	33				33
9	59	46	38	33	57	45	38	32	44	37	32	43	37	32	42	36	32	30				30
10	55	42	35	30	54	42	34	30	41	34	29	40	34	29	39	33	29	27				27

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P204784

CATALOG NUMBER: LE_6B20D010 EC6B10208035 6LBCSMW1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	111.0	3.9
10°-20°	315.9	11.0
20°-30°	475.2	16.6
30°-40°	563.2	19.6
40°-50°	560.5	19.5
50°-60°	451.8	15.8
60°-70°	273.3	9.5
70°-80°	101.5	3.5
80°-90°	15.1	0.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	902.1	31.5
0°-40°	1465.2	51.1
0°-60°	2477.5	86.4
0°-90°	2867.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2867.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1171	
5°	1166	111
15°	1119	316
25°	1032	475
35°	902	563
45°	730	560
55°	504	452
65°	274	273
75°	92	102
85°	12	15
90°	0	



TEST NUMBER: P204784

CATALOG NUMBER: LE_6B20D010 EC6B10208035 6LBCSMW1

CANDELA DISTRIBUTION (FULL):

	0°
0°	1171.1
2.5°	1171.1
5°	1165.9
7.5°	1162.5
10°	1152.0
12.5°	1134.6
15°	1119.0
17.5°	1101.6
20°	1080.8
22.5°	1060.0
25°	1032.1
27.5°	1002.6
30°	969.6
32.5°	938.2
35°	901.9
37.5°	863.6
40°	818.4
42.5°	775.0
45°	729.8
47.5°	679.4
50°	623.8
52.5°	566.5
55°	503.9
57.5°	448.2
60°	385.8
62.5°	330.1
65°	274.5
67.5°	222.4
70°	173.8
72.5°	130.4
75°	92.1
77.5°	59.1
80°	34.8
82.5°	20.9
85°	12.1
87.5°	5.2
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)