

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P203661

Luminaire Tested: **LE_6B30D010 EC6B30508030 6LBNH1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P203661
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LE_6B30D010 EC6B30508030 6LBNH1
Description: PORTFOLIO 6 INCH 50 DEGREE CUTOFF RECESSED DOWNLIGHT
NARROW DISTRIBUTION WITH SEMI-SPECULAR CLEAR TRIM
WATTAGE D010TR-27.4 W DE010-27.95 W D5LT-27.65 W DMX-27.73 W DL2-29.56 W
DL3-29.67 W DLE-29.73 W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2323.3 lumens
Efficiency: N/A
Efficacy: 83.0 lumens/watt
Spacing Criteria (0/90/45): 0.78 / 0.78 / 0.84
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 28
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P203661

CATALOG NUMBER: LE_6B30D010 EC6B30508030 6LBNH1

Luminous Intensity Polar Plot





TEST NUMBER: P203661

CATALOG NUMBER: LE_6B30D010 EC6B30508030 6LBNH1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	113	111	108	106	111	109	106	104	104	103	101	101	99	98	97	96	95	93			
2	108	103	99	96	106	101	98	94	98	95	92	95	93	90	92	90	89	87			
3	102	96	91	87	100	95	90	86	92	88	85	90	86	84	87	85	82	81			
4	97	90	84	80	95	89	83	79	86	82	78	84	81	78	83	79	77	75			
5	92	84	78	74	91	83	78	73	81	76	73	80	75	72	78	74	72	70			
6	88	79	73	69	86	78	72	68	77	72	68	75	71	67	74	70	67	65			
7	83	74	68	64	82	73	68	64	72	67	63	71	66	63	70	66	63	61			
8	79	70	64	60	78	69	64	60	68	63	59	67	63	59	66	62	59	58			
9	76	66	60	56	75	66	60	56	65	59	56	64	59	56	63	59	55	54			
10	72	62	57	53	71	62	57	53	61	56	53	60	56	52	60	55	52	51			

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P203661

CATALOG NUMBER: LE_6B30D010 EC6B30508030 6LBNH1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	267.8	11.5
10°-20°	638.7	27.5
20°-30°	731.7	31.5
30°-40°	491.6	21.2
40°-50°	140.5	6.0
50°-60°	34.3	1.5
60°-70°	13.1	0.6
70°-80°	5.0	0.2
80°-90°	0.6	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1638.2	70.5
0°-40°	2129.8	91.7
0°-60°	2304.6	99.2
0°-90°	2323.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2323.3	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2978	
5°	2894	268
15°	2292	639
25°	1597	732
35°	784	492
45°	161	140
55°	38	34
65°	13	13
75°	4	5
85°	0	1
90°	0	



TEST NUMBER: P203661

CATALOG NUMBER: LE_6B30D010 EC6B30508030 6LBNH1

CANDELA DISTRIBUTION (FULL):

	0°
0°	2978.2
2.5°	2957.1
5°	2893.6
7.5°	2779.1
10°	2639.4
12.5°	2461.5
15°	2292.0
17.5°	2114.0
20°	1936.1
22.5°	1766.6
25°	1597.1
27.5°	1440.4
30°	1258.2
32.5°	1016.8
35°	783.8
37.5°	571.9
40°	394.0
42.5°	258.4
45°	161.0
47.5°	97.5
50°	59.2
52.5°	46.6
55°	38.1
57.5°	29.6
60°	21.1
62.5°	17.0
65°	12.8
67.5°	8.5
70°	8.5
72.5°	4.2
75°	4.2
77.5°	4.2
80°	4.2
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)