

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P205227

Luminaire Tested: **LE_6B40D010 EC6B30509730 6LBWLI1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P205227
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LE_6B40D010 EC6B30509730 6LBWL1
Description: PORTFOLIO 6 INCH 60 DEGREE CUTOFF RECESSED DOWNLIGHT
WIDE DISTRIBUTION WITH SPECULAR CLEAR TRIM
WATTAGE D010TR-43.02 W DE010-42.54 W D5LT-42.539 W DMX-41.87 W DL2-41.57
W DL3-44.71 W DLE-39.33 W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3939.2 lumens
Efficiency: N/A
Efficacy: 94.2 lumens/watt
Spacing Criteria (0/90/45): 1.24 / 1.24 / 1.18
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 41.8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P205227

CATALOG NUMBER: LE_6B40D010 EC6B30509730 6LBWL11

Luminous Intensity Polar Plot





TEST NUMBER: P205227

CATALOG NUMBER: LE_6B40D010 EC6B30509730 6LBWLI1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				20	
RC	80				70				50				30				10				0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0	
RCR																						
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100				100
1	113	110	107	104	110	107	105	103	103	101	99	100	98	97	96	95	94	92				92
2	106	101	96	92	104	99	95	91	95	92	89	92	90	87	90	87	85	83				83
3	100	92	87	82	97	91	86	81	88	84	80	86	82	79	83	80	77	76				76
4	93	85	78	73	92	84	78	73	81	76	72	79	75	71	77	74	70	69				69
5	88	78	71	66	86	77	71	66	75	70	65	73	69	65	72	68	64	63				63
6	82	72	65	60	81	71	65	60	70	64	59	68	63	59	67	62	59	57				57
7	77	67	60	55	76	66	59	55	65	59	54	63	58	54	62	57	54	52				52
8	73	62	55	50	71	61	55	50	60	54	50	59	54	50	58	53	49	48				48
9	69	57	51	46	67	57	50	46	56	50	46	55	50	46	54	49	46	44				44
10	65	54	47	43	64	53	47	42	52	46	42	51	46	42	51	46	42	41				41

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P205227

CATALOG NUMBER: LE_6B40D010 EC6B30509730 6LBWLI1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	237.4	6.0
10°-20°	713.6	18.1
20°-30°	1075.7	27.3
30°-40°	1101.0	27.9
40°-50°	641.4	16.3
50°-60°	147.3	3.7
60°-70°	18.1	0.5
70°-80°	4.7	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2026.7	51.4
0°-40°	3127.6	79.4
0°-60°	3916.4	99.4
0°-90°	3939.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3939.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2461	
5°	2474	237
15°	2528	714
25°	2358	1076
35°	1786	1101
45°	826	641
55°	143	147
65°	13	18
75°	4	5
85°	0	0
90°	0	



TEST NUMBER: P205227

CATALOG NUMBER: LE_6B40D010 EC6B30509730 6LBWLI1

CANDELA DISTRIBUTION (FULL):

0°	
0°	2460.9
2.5°	2456.5
5°	2474.4
7.5°	2492.1
10°	2514.5
12.5°	2519.0
15°	2527.9
17.5°	2519.0
20°	2496.6
22.5°	2425.2
25°	2358.2
27.5°	2251.0
30°	2112.5
32.5°	1969.6
35°	1786.5
37.5°	1581.1
40°	1353.2
42.5°	1098.8
45°	826.2
47.5°	576.1
50°	379.6
52.5°	241.1
55°	142.9
57.5°	75.9
60°	40.2
62.5°	22.4
65°	13.4
67.5°	13.4
70°	8.9
72.5°	4.5
75°	4.5
77.5°	4.5
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)