

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P202647

Luminaire Tested: **LE_6B40D010 EC6B30508050 6LBMWMH1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P202647
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LE_6B40D010 EC6B30508050 6LBMWMH1
Description: PORTFOLIO 6 INCH 50 DEGREE CUTOFF RECESSED DOWNLIGHT
MEDIUM DISTRIBUTION WITH WARM HAZE TRIM
WATTAGE D010TR-43.02 W DE010-42.54 W D5LT-42.539 W DMX-41.87 W DL2-41.57
W DL3-44.71 W DLE-39.33 W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 4241.2 lumens
Efficiency: N/A
Efficacy: 101.5 lumens/watt
Spacing Criteria (0/90/45): 0.9 / 0.9 / 0.89
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 41.8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P202647

CATALOG NUMBER: LE_6B40D010 EC6B30508050 6LBMWMH1

Luminous Intensity Polar Plot





TEST NUMBER: P202647

CATALOG NUMBER: LE_6B40D010 EC6B30508050 6LBMWMH1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	113	111	108	106	111	108	106	104	104	103	101	101	99	98	97	96	95	93			
2	108	103	99	95	105	101	97	94	98	95	92	95	92	90	92	90	88	86			
3	102	95	90	86	100	94	89	86	91	88	84	89	86	83	87	84	82	80			
4	97	89	83	79	95	88	83	79	86	81	78	84	80	77	82	79	76	74			
5	92	83	77	73	90	82	77	73	80	76	72	79	75	71	77	74	71	69			
6	87	78	72	67	85	77	71	67	76	71	67	74	70	66	73	69	66	64			
7	83	73	67	63	81	72	67	63	71	66	62	70	65	62	69	65	61	60			
8	78	69	63	58	77	68	62	58	67	62	58	66	61	58	65	61	58	56			
9	75	65	59	55	73	64	59	55	63	58	54	62	58	54	62	57	54	53			
10	71	61	55	51	70	61	55	51	60	55	51	59	54	51	58	54	51	50			

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P202647

CATALOG NUMBER: LE_6B40D010 EC6B30508050 6LBMWMH1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	432.9	10.2
10°-20°	1111.3	26.2
20°-30°	1364.9	32.2
30°-40°	935.9	22.1
40°-50°	300.8	7.1
50°-60°	61.0	1.4
60°-70°	24.0	0.6
70°-80°	9.0	0.2
80°-90°	1.5	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2909.1	68.6
0°-40°	3845.0	90.7
0°-60°	4206.8	99.2
0°-90°	4241.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4241.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	4717	
5°	4627	433
15°	3976	1111
25°	3011	1365
35°	1493	936
45°	356	301
55°	61	61
65°	25	24
75°	7	9
85°	0	1
90°	0	



TEST NUMBER: P202647

CATALOG NUMBER: LE_6B40D010 EC6B30508050 6LBMWMH1

CANDELA DISTRIBUTION (FULL):

	0°
0°	4716.6
2.5°	4687.8
5°	4626.6
7.5°	4511.5
10°	4356.8
12.5°	4166.1
15°	3975.5
17.5°	3763.1
20°	3529.4
22.5°	3284.8
25°	3011.2
27.5°	2709.0
30°	2327.8
32.5°	1906.8
35°	1493.0
37.5°	1115.2
40°	802.2
42.5°	546.9
45°	356.1
47.5°	219.5
50°	133.1
52.5°	82.8
55°	61.1
57.5°	46.8
60°	36.0
62.5°	28.8
65°	25.1
67.5°	18.0
70°	14.4
72.5°	10.8
75°	7.2
77.5°	7.2
80°	3.6
82.5°	3.6
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)