

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P202558

Luminaire Tested: **LE_6B50D010R EC6B30509024 6LBSWMH1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P202558
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LE_6B50D010R EC6B30509024 6LBSWMH1
Description: PORTFOLIO 6 INCH SHALLOW RECESSED DOWNLIGHT
SHALLOW DISTRIBUTION WITH WARM HAZE TRIM
SINGLE DRIVER D010TE
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 5073.8 lumens
Efficiency: N/A
Efficacy: 86.3 lumens/watt
Spacing Criteria (0/90/45): 0.97 / 0.97 / 1.1
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 58.8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P202558

CATALOG NUMBER: LE_6B50D010R EC6B30509024 6LBSWMH1

Luminous Intensity Polar Plot





TEST NUMBER: P202558

CATALOG NUMBER: LE_6B50D010R EC6B30509024 6LBSWMH1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	111	107	104	101	108	105	102	99	101	98	96	97	95	93	94	92	90	88			
2	103	96	90	85	100	94	89	84	91	86	82	87	84	81	84	81	79	77			
3	95	86	79	73	92	84	78	73	81	76	71	79	74	70	76	72	69	67			
4	88	77	70	64	86	76	69	63	74	67	62	71	66	62	69	65	61	59			
5	81	70	62	56	79	69	61	56	67	60	55	65	59	55	63	58	54	52			
6	76	64	56	50	74	63	55	50	61	54	49	59	53	49	58	53	48	47			
7	70	58	50	45	69	57	50	45	56	49	44	55	48	44	53	48	44	42			
8	66	54	46	40	64	53	45	40	52	45	40	50	44	40	49	44	40	38			
9	62	49	42	37	61	49	42	37	48	41	37	47	41	36	46	40	36	35			
10	58	46	39	34	57	45	38	34	45	38	34	44	38	33	43	37	33	32			

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P202558

CATALOG NUMBER: LE_6B50D010R EC6B30509024 6LBSWMH1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	271.5	5.4
10°-20°	709.6	14.0
20°-30°	940.9	18.5
30°-40°	1003.6	19.8
40°-50°	938.2	18.5
50°-60°	715.3	14.1
60°-70°	389.1	7.7
70°-80°	104.3	2.1
80°-90°	1.3	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1922.0	37.9
0°-40°	2925.6	57.7
0°-60°	4579.1	90.2
0°-90°	5073.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5073.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2934	
5°	2894	271
15°	2530	710
25°	2048	941
35°	1604	1004
45°	1222	938
55°	805	715
65°	388	389
75°	90	104
85°	0	1
90°	0	



TEST NUMBER: P202558

CATALOG NUMBER: LE_6B50D010R EC6B30509024 6LBSWMH1

CANDELA DISTRIBUTION (FULL):

	0°
0°	2934.0
2.5°	2924.6
5°	2893.6
7.5°	2828.4
10°	2753.8
12.5°	2648.0
15°	2530.0
17.5°	2411.9
20°	2284.4
22.5°	2163.2
25°	2048.2
27.5°	1927.0
30°	1812.0
32.5°	1700.1
35°	1603.8
37.5°	1507.4
40°	1408.0
42.5°	1317.8
45°	1221.5
47.5°	1115.8
50°	1016.4
52.5°	910.6
55°	805.0
57.5°	690.0
60°	584.2
62.5°	484.9
65°	388.5
67.5°	301.5
70°	220.6
72.5°	152.2
75°	90.1
77.5°	40.4
80°	9.4
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)