

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P204110

Luminaire Tested: **LE_6B50D010R EC6B30509730 6LBNMW1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P204110
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LE_6B50D010R EC6B30509730 6LBNMW1
Description: PORTFOLIO 6 INCH 50 DEGREE CUTOFF RECESSED DOWNLIGHT
NARROW DISTRIBUTION WITH MATTE WHITE TRIM
SINGLE DRIVER D010TE
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3600.0 lumens
Efficiency: N/A
Efficacy: 61.2 lumens/watt
Spacing Criteria (0/90/45): 0.99 / 0.99 / 0.97
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 58.8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P204110

CATALOG NUMBER: LE_6B50D010R EC6B30509730 6LBNMW1

Luminous Intensity Polar Plot





TEST NUMBER: P204110

CATALOG NUMBER: LE_6B50D010R EC6B30509730 6LBNMW1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									20																	
RC	80									70									50									30									10									0								
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																								
RCR																																																						
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																																				
1	112	108	105	103	109	106	103	101	102	100	98	98	97	95	95	93	92	90																																				
2	105	99	94	90	102	97	92	89	94	90	87	91	87	85	88	85	83	81																																				
3	98	90	84	79	96	89	83	79	86	81	77	84	80	76	81	78	75	73																																				
4	92	83	76	71	90	82	76	71	80	74	70	77	73	69	75	71	68	66																																				
5	87	77	70	64	85	76	69	64	74	68	64	72	67	63	70	66	62	61																																				
6	81	71	64	59	80	70	63	59	68	63	58	67	62	58	66	61	57	56																																				
7	77	66	59	54	75	65	59	54	64	58	54	63	57	53	61	57	53	51																																				
8	72	61	55	50	71	61	54	50	60	54	49	59	53	49	58	53	49	47																																				
9	69	58	51	46	67	57	51	46	56	50	46	55	50	46	54	49	46	44																																				
10	65	54	47	43	64	54	47	43	53	47	43	52	46	43	51	46	43	41																																				

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P204110

CATALOG NUMBER: LE_6B50D010R EC6B30509730 6LBNMW1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	274.2	7.6
10°-20°	726.7	20.2
20°-30°	970.2	26.9
30°-40°	782.7	21.7
40°-50°	375.1	10.4
50°-60°	222.3	6.2
60°-70°	147.8	4.1
70°-80°	79.2	2.2
80°-90°	21.8	0.6
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1971.0	54.8
0°-40°	2753.8	76.5
0°-60°	3351.2	93.1
0°-90°	3600.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3600.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2952	
5°	2918	274
15°	2586	727
25°	2123	970
35°	1253	783
45°	464	375
55°	246	222
65°	149	148
75°	74	79
85°	17	22
90°	0	



TEST NUMBER: P204110

CATALOG NUMBER: LE_6B50D010R EC6B30509730 6LBNMW1

CANDELA DISTRIBUTION (FULL):

	0°
0°	2952.4
2.5°	2952.4
5°	2918.0
7.5°	2860.9
10°	2780.8
12.5°	2694.9
15°	2586.2
17.5°	2483.2
20°	2368.8
22.5°	2248.6
25°	2122.8
27.5°	1991.1
30°	1802.4
32.5°	1539.1
35°	1253.0
37.5°	989.9
40°	766.8
42.5°	595.0
45°	463.5
47.5°	366.1
50°	309.0
52.5°	274.6
55°	246.0
57.5°	223.1
60°	194.5
62.5°	171.6
65°	148.8
67.5°	125.9
70°	108.8
72.5°	91.5
75°	74.4
77.5°	57.2
80°	45.8
82.5°	34.4
85°	17.1
87.5°	5.8
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)