

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P203183

Luminaire Tested: **LE_6B50D010R EC6B30509730 6LBWMW1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P203183
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LE_6B50D010R EC6B30509730 6LBWMW1
Description: PORTFOLIO 6 INCH 60 DEGREE CUTOFF RECESSED DOWNLIGHT
WIDE DISTRIBUTION WITH MATTE WHITE TRIM
SINGLE DRIVER D010TE
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 4714.3 lumens
Efficiency: N/A
Efficacy: 80.2 lumens/watt
Spacing Criteria (0/90/45): 1.13 / 1.13 / 1.15
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 58.8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P203183

CATALOG NUMBER: LE_6B50D010R EC6B30509730 6LBWMW1

Luminous Intensity Polar Plot





TEST NUMBER: P203183

CATALOG NUMBER: LE_6B50D010R EC6B30509730 6LBWMW1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	111	107	104	100	108	105	102	99	101	98	96	97	95	93	93	92	90	88																			
2	103	96	90	86	100	94	89	85	91	86	83	88	84	81	85	82	79	77																			
3	95	86	80	74	93	85	79	74	82	77	72	80	75	71	77	73	70	68																			
4	89	78	71	65	86	77	70	65	75	69	64	72	67	63	70	66	62	60																			
5	82	71	64	58	80	70	63	58	68	62	57	66	61	56	65	60	56	54																			
6	77	65	57	52	75	64	57	52	63	56	51	61	55	51	60	54	50	49																			
7	72	60	52	47	70	59	52	47	58	51	46	56	50	46	55	50	46	44																			
8	67	55	48	42	66	55	47	42	53	47	42	52	46	42	51	46	42	40																			
9	63	51	44	39	62	51	44	39	50	43	39	49	43	38	48	42	38	37																			
10	60	48	40	36	58	47	40	36	46	40	36	45	40	35	45	39	35	34																			

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P203183

CATALOG NUMBER: LE_6B50D010R EC6B30509730 6LBWMW1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	249.3	5.3
10°-20°	699.2	14.8
20°-30°	1007.4	21.4
30°-40°	1046.0	22.2
40°-50°	773.3	16.4
50°-60°	461.9	9.8
60°-70°	280.7	6.0
70°-80°	153.8	3.3
80°-90°	42.7	0.9
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1955.9	41.5
0°-40°	3001.9	63.7
0°-60°	4237.1	89.9
0°-90°	4714.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4714.3	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2647	
5°	2630	249
15°	2482	699
25°	2196	1007
35°	1687	1046
45°	995	773
55°	503	462
65°	280	281
75°	143	154
85°	34	43
90°	0	



TEST NUMBER: P203183

CATALOG NUMBER: LE_6B50D010R EC6B30509730 6LBWMW1

CANDELA DISTRIBUTION (FULL):

	0°
0°	2647.4
2.5°	2647.4
5°	2630.2
7.5°	2607.4
10°	2573.0
12.5°	2533.0
15°	2481.5
17.5°	2424.4
20°	2367.2
22.5°	2287.1
25°	2195.6
27.5°	2098.5
30°	1972.6
32.5°	1846.9
35°	1686.8
37.5°	1521.0
40°	1338.0
42.5°	1160.8
45°	994.9
47.5°	846.2
50°	714.8
52.5°	600.4
55°	503.1
57.5°	428.9
60°	366.0
62.5°	320.2
65°	280.1
67.5°	245.9
70°	211.5
72.5°	177.2
75°	143.0
77.5°	114.4
80°	85.8
82.5°	62.9
85°	34.2
87.5°	17.1
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)