

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P205029

Luminaire Tested: **LE\_6B50D010R EC6B30508040 6LBCS1MMS**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-41-14  
Report Number: P205029  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)  
Test Lab: INNOVATION CENTER-P3  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: PORTFOLIO  
Catalog Number: LE\_6B50D010R EC6B30508040 6LBCS1MMS  
Description: PORTFOLIO 6 INCH SHALLOW RECESSED DOWNLIGHT  
SHALLOW DISTRIBUTION WITH CAST MATTE METALLIC SILVER TRIM  
SINGLE DRIVER D010TE  
Light Source: HIGH LUMEN LED  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 7117.9 lumens  
Efficiency: N/A  
Efficacy: 121.1 lumens/watt  
Spacing Criteria (0/90/45): 1.16 / 1.16 / 1.27  
Luminous Opening: Point Source (0' x 0' x 0')  
CIE Type: Direct


Input Watts (W): 58.8  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P205029

CATALOG NUMBER: LE\_6B50D010R EC6B30508040 6LBSC1MMS

### Luminous Intensity Polar Plot





TEST NUMBER: P205029

CATALOG NUMBER: LE\_6B50D010R EC6B30508040 6LBSC1MMS

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	111	107	103	100	108	105	101	98	100	98	95	97	94	92	93	91	90	88																			
2	102	95	89	84	99	93	88	83	90	85	81	86	83	79	83	80	78	76																			
3	94	85	77	72	92	83	76	71	80	74	70	77	73	69	75	71	67	65																			
4	87	76	68	62	84	74	67	61	72	66	61	70	64	60	68	63	59	57																			
5	80	68	60	54	78	67	59	54	65	58	53	63	57	53	61	56	52	50																			
6	74	62	54	48	72	61	53	47	59	52	47	58	51	47	56	51	46	44																			
7	69	56	48	42	67	56	48	42	54	47	42	53	46	42	51	46	41	40																			
8	64	52	44	38	63	51	43	38	50	43	38	48	42	38	47	42	37	36																			
9	60	48	40	35	59	47	40	34	46	39	34	45	39	34	44	38	34	32																			
10	57	44	36	31	55	43	36	31	43	36	31	42	35	31	41	35	31	29																			

**AVERAGE LUMINANCE (cd/sqm):**





TEST NUMBER: P205029

CATALOG NUMBER: LE\_6B50D010R EC6B30508040 6LBCS1MMS

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	308.1	4.3
10°-20°	864.4	12.1
20°-30°	1262.5	17.7
30°-40°	1444.0	20.3
40°-50°	1387.8	19.5
50°-60°	1071.6	15.1
60°-70°	598.1	8.4
70°-80°	174.0	2.4
80°-90°	7.5	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2434.9	34.2
0°-40°	3878.9	54.5
0°-60°	6338.2	89.0
0°-90°	7117.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	7117.9	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	3269	
5°	3241	308
15°	3066	864
25°	2744	1262
35°	2311	1444
45°	1809	1388
55°	1202	1072
65°	598	598
75°	152	174
85°	5	7
90°	0	



TEST NUMBER: P205029

CATALOG NUMBER: LE\_6B50D010R EC6B30508040 6LBCS1MMS

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	3268.8
2.5°	3268.8
5°	3241.1
7.5°	3227.4
10°	3181.2
12.5°	3126.0
15°	3066.1
17.5°	3006.4
20°	2918.9
22.5°	2849.8
25°	2743.9
27.5°	2638.0
30°	2532.1
32.5°	2426.2
35°	2311.1
37.5°	2196.0
40°	2062.5
42.5°	1942.9
45°	1809.4
47.5°	1657.4
50°	1514.6
52.5°	1358.1
55°	1201.6
57.5°	1040.5
60°	888.5
62.5°	736.6
65°	598.5
67.5°	469.6
70°	349.9
72.5°	244.0
75°	151.9
77.5°	78.2
80°	27.6
82.5°	9.2
85°	4.6
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093







— 0°-180°







(END OF REPORT)