

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P204617

Luminaire Tested: **LE_6B50D010R EC6B30508040 6LBSMW1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P204617
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LE_6B50D010R EC6B30508040 6LBSMW1
Description: PORTFOLIO 6 INCH SHALLOW RECESSED DOWNLIGHT
SHALLOW DISTRIBUTION WITH MATTE WHITE TRIM
SINGLE DRIVER D010TE
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 7516.6 lumens
Efficiency: N/A
Efficacy: 127.8 lumens/watt
Spacing Criteria (0/90/45): 1.24 / 1.24 / 1.34
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 58.8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P204617

CATALOG NUMBER: LE_6B50D010R EC6B30508040 6LBSMW1

Luminous Intensity Polar Plot





TEST NUMBER: P204617

CATALOG NUMBER: LE_6B50D010R EC6B30508040 6LBSMW1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				20	
RC	80				70				50				30				10				0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0	
RCR																						
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100				100
1	110	106	102	99	107	104	100	97	99	97	94	96	93	91	92	90	88	86				86
2	101	93	87	82	98	92	86	81	88	83	79	85	81	77	82	79	76	74				74
3	93	83	75	69	90	81	74	69	78	72	67	76	70	66	73	69	65	63				63
4	85	74	66	59	83	72	65	59	70	63	58	68	62	57	66	61	56	54				54
5	78	66	58	51	76	65	57	51	63	56	51	61	55	50	59	54	49	47				47
6	73	60	51	45	71	59	51	45	57	50	44	55	49	44	54	48	44	42				42
7	67	54	46	40	66	54	46	40	52	45	40	51	44	39	49	43	39	37				37
8	63	50	41	36	61	49	41	36	48	41	35	46	40	35	45	39	35	33				33
9	59	46	38	32	57	45	37	32	44	37	32	43	36	32	42	36	32	30				30
10	55	42	34	29	54	42	34	29	41	34	29	40	33	29	39	33	29	27				27

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P204617

CATALOG NUMBER: LE_6B50D010R EC6B30508040 6LBSMW1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	286.9	3.8
10°-20°	818.0	10.9
20°-30°	1231.9	16.4
30°-40°	1465.8	19.5
40°-50°	1463.1	19.5
50°-60°	1189.9	15.8
60°-70°	732.0	9.7
70°-80°	283.5	3.8
80°-90°	45.4	0.6
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2336.8	31.1
0°-40°	3802.5	50.6
0°-60°	6455.6	85.9
0°-90°	7516.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	7516.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3028	
5°	3020	287
15°	2904	818
25°	2681	1232
35°	2347	1466
45°	1902	1463
55°	1332	1190
65°	735	732
75°	258	284
85°	36	45
90°	0	



TEST NUMBER: P204617

CATALOG NUMBER: LE_6B50D010R EC6B30508040 6LBSMW1

CANDELA DISTRIBUTION (FULL):

0°	
0°	3028.5
2.5°	3032.9
5°	3019.5
7.5°	3001.8
10°	2979.5
12.5°	2939.4
15°	2903.8
17.5°	2850.4
20°	2792.4
22.5°	2739.0
25°	2681.1
27.5°	2600.9
30°	2520.8
32.5°	2445.0
35°	2347.0
37.5°	2240.1
40°	2142.2
42.5°	2022.0
45°	1901.8
47.5°	1772.5
50°	1634.5
52.5°	1492.0
55°	1331.6
57.5°	1175.8
60°	1024.4
62.5°	877.4
65°	734.9
67.5°	601.2
70°	476.5
72.5°	360.8
75°	258.2
77.5°	169.2
80°	102.4
82.5°	62.4
85°	35.6
87.5°	17.9
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)