

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P203901

Luminaire Tested: **LE\_6B50D010R EC6B30509040 6LBNGPH1**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-41-14  
Report Number: P203901  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)  
Test Lab: INNOVATION CENTER-P3  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: PORTFOLIO  
Catalog Number: LE\_6B50D010R EC6B30509040 6LBNGPH1  
Description: PORTFOLIO 6 INCH 50 DEGREE CUTOFF RECESSED DOWNLIGHT  
NARROW DISTRIBUTION WITH GRAPHITE HAZE TRIM  
SINGLE DRIVER D010TE  
Light Source: HIGH LUMEN LED  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 2915.8 lumens  
Efficiency: N/A  
Efficacy: 49.6 lumens/watt  
Spacing Criteria (0/90/45): 0.84 / 0.84 / 0.88  
Luminous Opening: Point Source (0' x 0' x 0')  
CIE Type: Direct


Input Watts (W): 58.8  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P203901

CATALOG NUMBER: LE\_6B50D010R EC6B30509040 6LBNGPH1

### Luminous Intensity Polar Plot





TEST NUMBER: P203901

CATALOG NUMBER: LE\_6B50D010R EC6B30509040 6LBNGPH1

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20			
RC	80				70				50				30				10		0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	114	111	108	106	111	109	106	104	105	103	101	101	100	98	97	96	95	94		
2	108	103	99	96	106	101	98	95	98	95	93	95	93	91	92	91	89	87		
3	103	96	91	87	101	95	90	87	92	88	85	90	87	84	88	85	83	81		
4	97	90	84	80	96	89	84	80	87	82	79	85	81	78	83	80	77	76		
5	93	84	78	74	91	83	78	74	82	77	73	80	76	73	78	75	72	70		
6	88	79	73	69	86	78	73	69	77	72	68	75	71	68	74	70	67	66		
7	84	74	68	64	82	74	68	64	72	67	64	71	67	63	70	66	63	62		
8	80	70	64	60	78	69	64	60	68	63	60	67	63	59	66	62	59	58		
9	76	66	60	56	75	66	60	56	65	60	56	64	59	56	63	59	56	54		
10	72	63	57	53	71	62	57	53	61	56	53	61	56	53	60	56	52	51		

**AVERAGE LUMINANCE (cd/sqm):**





TEST NUMBER: P203901

CATALOG NUMBER: LE\_6B50D010R EC6B30509040 6LBNGPH1

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	320.8	11.0
10°-20°	791.3	27.1
20°-30°	958.8	32.9
30°-40°	653.4	22.4
40°-50°	155.6	5.3
50°-60°	24.3	0.8
60°-70°	8.9	0.3
70°-80°	2.6	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2070.9	71.0
0°-40°	2724.3	93.4
0°-60°	2904.2	99.6
0°-90°	2915.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2915.8	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	3544	
5°	3445	321
15°	2833	791
25°	2095	959
35°	1044	653
45°	166	156
55°	27	24
65°	7	9
75°	0	3
85°	0	0
90°	0	



TEST NUMBER: P203901

CATALOG NUMBER: LE\_6B50D010R EC6B30509040 6LBNGPH1

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	3544.4
2.5°	3524.4
5°	3444.6
7.5°	3338.1
10°	3185.2
12.5°	3012.4
15°	2832.8
17.5°	2646.6
20°	2460.4
22.5°	2274.2
25°	2094.6
27.5°	1928.4
30°	1689.0
32.5°	1376.5
35°	1044.0
37.5°	744.8
40°	492.1
42.5°	305.9
45°	166.2
47.5°	86.5
50°	46.5
52.5°	33.2
55°	26.6
57.5°	20.0
60°	13.2
62.5°	13.2
65°	6.6
67.5°	6.6
70°	6.6
72.5°	6.6
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093







— 0°-180°







(END OF REPORT)