

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P204519

Luminaire Tested: **LE_6B50D010R EC6B30509040 6LBSB1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P204519
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LE_6B50D010R EC6B30509040 6LBSB1
Description: PORTFOLIO 6 INCH SHALLOW RECESSED DOWNLIGHT
SHALLOW DISTRIBUTION WITH SPECULAR BLACK TRIM
SINGLE DRIVER D010TE
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 5307.1 lumens
Efficiency: N/A
Efficacy: 90.3 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 1.2 / 1.3
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 58.8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P204519

CATALOG NUMBER: LE_6B50D010R EC6B30509040 6LBSB1

Luminous Intensity Polar Plot





TEST NUMBER: P204519

CATALOG NUMBER: LE_6B50D010R EC6B30509040 6LBSB1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	111	107	103	100	108	105	101	98	100	98	95	97	94	93	93	91	90	88																			
2	102	95	89	84	100	93	88	83	90	85	81	86	83	79	84	80	78	76																			
3	94	84	77	72	91	83	76	71	80	74	70	77	73	68	75	71	67	65																			
4	86	76	68	62	84	74	67	61	72	65	60	70	64	60	68	63	59	57																			
5	80	68	60	54	78	67	59	53	65	58	53	63	57	52	61	56	52	50																			
6	74	62	53	47	72	61	53	47	59	52	47	57	51	46	56	50	46	44																			
7	69	56	48	42	67	55	48	42	54	47	42	52	46	41	51	45	41	39																			
8	64	51	43	38	63	51	43	38	49	42	37	48	42	37	47	41	37	35																			
9	60	47	39	34	59	47	39	34	46	39	34	45	38	34	44	38	34	32																			
10	56	44	36	31	55	43	36	31	42	36	31	41	35	31	40	35	31	29																			

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P204519

CATALOG NUMBER: LE_6B50D010R EC6B30509040 6LBSB1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	221.0	4.2
10°-20°	626.9	11.8
20°-30°	932.6	17.6
30°-40°	1085.3	20.4
40°-50°	1057.8	19.9
50°-60°	813.6	15.3
60°-70°	449.8	8.5
70°-80°	119.1	2.2
80°-90°	0.9	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1780.5	33.5
0°-40°	2865.8	54.0
0°-60°	4737.2	89.3
0°-90°	5307.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5307.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2341	
5°	2328	221
15°	2220	627
25°	2025	933
35°	1742	1085
45°	1372	1058
55°	908	814
65°	451	450
75°	101	119
85°	0	1
90°	0	



TEST NUMBER: P204519

CATALOG NUMBER: LE_6B50D010R EC6B30509040 6LBSB1

CANDELA DISTRIBUTION (FULL):

	0°
0°	2341.1
2.5°	2341.1
5°	2327.6
7.5°	2307.5
10°	2294.0
12.5°	2253.6
15°	2220.0
17.5°	2186.4
20°	2139.2
22.5°	2092.2
25°	2025.0
27.5°	1957.6
30°	1890.4
32.5°	1816.4
35°	1742.4
37.5°	1648.2
40°	1567.5
42.5°	1480.0
45°	1372.4
47.5°	1271.5
50°	1157.1
52.5°	1036.0
55°	908.2
57.5°	787.1
60°	672.8
62.5°	558.4
65°	450.8
67.5°	349.9
70°	255.6
72.5°	174.9
75°	100.9
77.5°	47.1
80°	6.8
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)