

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P204514

Luminaire Tested: **LE_6B50D010R EC6B30508050 6LBSB1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P204514
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LE_6B50D010R EC6B30508050 6LBSB1
Description: PORTFOLIO 6 INCH SHALLOW RECESSED DOWNLIGHT
SHALLOW DISTRIBUTION WITH SPECULAR BLACK TRIM
SINGLE DRIVER D010TE
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 6331.7 lumens
Efficiency: N/A
Efficacy: 107.7 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 1.2 / 1.3
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 58.8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P204514

CATALOG NUMBER: LE_6B50D010R EC6B30508050 6LBSB1

Luminous Intensity Polar Plot





TEST NUMBER: P204514

CATALOG NUMBER: LE_6B50D010R EC6B30508050 6LBSB1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				20	
RC	80				70				50				30				10				0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0	
RCR																						
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100				100
1	111	107	103	100	108	105	101	98	100	98	95	97	94	93	93	91	90	88				88
2	102	95	89	84	100	93	88	83	90	85	81	86	83	79	84	80	78	76				76
3	94	84	77	72	91	83	76	71	80	74	70	77	73	68	75	71	67	65				65
4	86	76	68	62	84	74	67	61	72	65	60	70	64	60	68	63	59	57				57
5	80	68	60	54	78	67	59	53	65	58	53	63	57	52	61	56	52	50				50
6	74	62	53	47	72	61	53	47	59	52	47	57	51	46	56	50	46	44				44
7	69	56	48	42	67	55	48	42	54	47	42	52	46	41	51	45	41	39				39
8	64	51	43	38	63	51	43	38	49	42	37	48	42	37	47	41	37	35				35
9	60	47	39	34	59	47	39	34	46	39	34	45	38	34	44	38	34	32				32
10	56	44	36	31	55	43	36	31	42	36	31	41	35	31	40	35	31	29				29

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P204514

CATALOG NUMBER: LE_6B50D010R EC6B30508050 6LBSB1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	263.6	4.2
10°-20°	748.0	11.8
20°-30°	1112.7	17.6
30°-40°	1294.8	20.5
40°-50°	1262.1	19.9
50°-60°	970.7	15.3
60°-70°	536.6	8.5
70°-80°	142.1	2.2
80°-90°	1.1	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2124.3	33.6
0°-40°	3419.2	54.0
0°-60°	5651.9	89.3
0°-90°	6331.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6331.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2793	
5°	2777	264
15°	2649	748
25°	2416	1113
35°	2079	1295
45°	1637	1262
55°	1084	971
65°	538	537
75°	120	142
85°	0	1
90°	0	



TEST NUMBER: P204514

CATALOG NUMBER: LE_6B50D010R EC6B30508050 6LBSB1

CANDELA DISTRIBUTION (FULL):

	0°
0°	2793.1
2.5°	2793.1
5°	2777.1
7.5°	2753.0
10°	2737.0
12.5°	2688.9
15°	2648.6
17.5°	2608.5
20°	2552.4
22.5°	2496.1
25°	2415.9
27.5°	2335.6
30°	2255.4
32.5°	2167.1
35°	2078.9
37.5°	1966.5
40°	1870.1
42.5°	1765.8
45°	1637.4
47.5°	1517.0
50°	1380.5
52.5°	1236.0
55°	1083.5
57.5°	939.1
60°	802.6
62.5°	666.1
65°	537.8
67.5°	417.4
70°	305.0
72.5°	208.6
75°	120.4
77.5°	56.1
80°	8.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)