

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P203802

Luminaire Tested: **LE_6B60D010R EC6B60708027 6LBNWH1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P203802
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LE_6B60D010R EC6B60708027 6LBNWH1
Description: PORTFOLIO 6 INCH 50 DEGREE CUTOFF RECESSED DOWNLIGHT
NARROW DISTRIBUTION WITH WHEAT TRIM
SINGLE DRIVER D010TE
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 4810.5 lumens
Efficiency: N/A
Efficacy: 77.0 lumens/watt
Spacing Criteria (0/90/45): 0.56 / 0.56 / 0.64
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 62.5
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P203802

CATALOG NUMBER: LE_6B60D010R EC6B60708027 6LBNWH1

Luminous Intensity Polar Plot





TEST NUMBER: P203802

CATALOG NUMBER: LE_6B60D010R EC6B60708027 6LBNWH1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	114	111	109	107	112	109	107	105	105	104	102	101	100	99	98	97	96	94
2	109	104	101	97	107	103	99	96	99	97	94	96	94	92	94	92	90	89
3	104	98	93	90	102	97	92	89	94	91	88	92	89	86	89	87	85	83
4	99	92	87	83	97	91	86	83	89	85	82	87	84	81	85	82	80	79
5	95	87	82	78	93	86	81	77	84	80	77	83	79	76	81	78	75	74
6	91	82	77	73	89	82	76	73	80	76	72	79	75	72	78	74	71	70
7	87	78	73	69	85	77	72	69	76	72	68	75	71	68	74	70	67	66
8	83	74	69	65	82	74	68	65	73	68	65	72	67	64	71	67	64	63
9	79	71	65	62	78	70	65	61	69	65	61	68	64	61	68	64	61	60
10	76	67	62	58	75	67	62	58	66	61	58	65	61	58	65	61	58	57

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P203802

CATALOG NUMBER: LE_6B60D010R EC6B60708027 6LBNWH1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	799.5	16.6
10°-20°	1536.3	31.9
20°-30°	1396.6	29.0
30°-40°	846.6	17.6
40°-50°	192.7	4.0
50°-60°	24.6	0.5
60°-70°	11.1	0.2
70°-80°	3.2	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3732.4	77.6
0°-40°	4578.9	95.2
0°-60°	4796.2	99.7
0°-90°	4810.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4810.5	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	9445	
5°	8904	799
15°	5533	1536
25°	3028	1397
35°	1342	847
45°	213	193
55°	24	25
65°	8	11
75°	0	3
85°	0	0
90°	0	



TEST NUMBER: P203802

CATALOG NUMBER: LE_6B60D010R EC6B60708027 6LBNWH1

CANDELA DISTRIBUTION (FULL):

	0°
0°	9444.6
2.5°	9330.1
5°	8904.5
7.5°	8217.0
10°	7341.2
12.5°	6432.9
15°	5532.6
17.5°	4714.1
20°	4026.6
22.5°	3470.1
25°	3028.1
27.5°	2635.4
30°	2250.6
32.5°	1800.5
35°	1342.2
37.5°	941.2
40°	622.0
42.5°	384.6
45°	212.8
47.5°	98.2
50°	40.9
52.5°	32.8
55°	24.5
57.5°	24.5
60°	16.4
62.5°	16.4
65°	8.1
67.5°	8.1
70°	8.1
72.5°	8.1
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)