

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P203499

Luminaire Tested: **LE_6B60D010R EC6B60709027 6LBMB1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P203499
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LE_6B60D010R EC6B60709027 6LBMB1
Description: PORTFOLIO 6 INCH 50 DEGREE CUTOFF RECESSED DOWNLIGHT
MEDIUM DISTRIBUTION WITH SPECULAR BLACK TRIM
SINGLE DRIVER D010TE
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2669.5 lumens
Efficiency: N/A
Efficacy: 42.7 lumens/watt
Spacing Criteria (0/90/45): 0.85 / 0.85 / 0.86
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 62.5
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P203499

CATALOG NUMBER: LE_6B60D010R EC6B60709027 6LBMB1

Luminous Intensity Polar Plot





TEST NUMBER: P203499

CATALOG NUMBER: LE_6B60D010R EC6B60709027 6LBMB1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									20																	
RC	80									70									50									30									10									0								
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																					
RCR	0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																																			
	1	114	111	109	106	111	109	107	105	105	103	102	101	100	99	98	97	96	94																																			
	2	108	104	100	96	106	102	98	95	99	96	93	96	93	91	93	91	89	88																																			
	3	103	97	92	88	101	95	91	87	93	89	86	90	87	85	88	86	83	82																																			
	4	98	91	85	81	96	90	85	81	87	83	80	85	82	79	84	81	78	76																																			
	5	93	85	79	75	92	84	79	75	82	78	74	81	77	74	79	76	73	72																																			
	6	89	80	74	70	87	79	74	70	78	73	69	76	72	69	75	71	68	67																																			
	7	84	75	69	65	83	75	69	65	73	68	65	72	68	65	71	67	64	63																																			
	8	80	71	65	61	79	71	65	61	69	64	61	68	64	61	67	63	60	59																																			
	9	77	67	61	58	76	67	61	57	66	61	57	65	60	57	64	60	57	56																																			
	10	73	64	58	54	72	63	58	54	62	57	54	62	57	54	61	57	54	52																																			

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P203499

CATALOG NUMBER: LE_6B60D010R EC6B60709027 6LBMB1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	304.9	11.4
10°-20°	752.4	28.2
20°-30°	906.3	33.9
30°-40°	573.3	21.5
40°-50°	131.2	4.9
50°-60°	1.5	0.1
60°-70°	0.0	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1963.6	73.6
0°-40°	2536.8	95.0
0°-60°	2669.5	100.0
0°-90°	2669.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2669.5	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3361	
5°	3285	305
15°	2684	752
25°	2008	906
35°	904	573
45°	145	131
55°	0	1
65°	0	0
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P203499

CATALOG NUMBER: LE_6B60D010R EC6B60709027 6LBMB1

CANDELA DISTRIBUTION (FULL):

	0°
0°	3360.6
2.5°	3346.9
5°	3284.8
7.5°	3167.5
10°	3022.5
12.5°	2850.0
15°	2684.4
17.5°	2525.8
20°	2360.1
22.5°	2194.5
25°	2008.1
27.5°	1787.2
30°	1518.1
32.5°	1214.5
35°	904.0
37.5°	641.8
40°	434.8
42.5°	269.1
45°	144.9
47.5°	62.1
50°	13.8
52.5°	0.0
55°	0.0
57.5°	0.0
60°	0.0
62.5°	0.0
65°	0.0
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)