

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P204846

Luminaire Tested: **LE_6B60D010R EC6B60709730 6LBCSMW1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P204846
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LE_6B60D010R EC6B60709730 6LBCSMW1
Description: PORTFOLIO 6 INCH SHALLOW RECESSED DOWNLIGHT
SHALLOW DISTRIBUTION WITH CAST MATTE WHITE TRIM
SINGLE DRIVER D010TE
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 6120.6 lumens
Efficiency: N/A
Efficacy: 97.9 lumens/watt
Spacing Criteria (0/90/45): 1.23 / 1.23 / 1.33
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 62.5
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P204846

CATALOG NUMBER: LE_6B60D010R EC6B60709730 6LBSCMW1

Luminous Intensity Polar Plot





TEST NUMBER: P204846

CATALOG NUMBER: LE_6B60D010R EC6B60709730 6LBSCMW1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	110	106	102	99	108	104	100	97	100	97	94	96	93	91	92	90	89	87																			
2	101	94	87	82	99	92	86	81	88	84	79	85	81	78	82	79	76	74																			
3	93	83	75	70	90	81	74	69	79	73	68	76	71	67	73	69	65	63																			
4	85	74	66	60	83	73	65	59	70	64	58	68	62	58	66	61	57	55																			
5	79	66	58	52	77	65	57	51	63	56	51	61	55	50	60	54	50	48																			
6	73	60	52	45	71	59	51	45	57	50	45	56	49	44	54	49	44	42																			
7	68	55	46	40	66	54	46	40	52	45	40	51	44	40	50	44	39	37																			
8	63	50	42	36	61	49	41	36	48	41	36	47	40	36	46	40	35	33																			
9	59	46	38	33	57	45	38	32	44	37	32	43	37	32	42	36	32	30																			
10	55	42	35	30	54	42	34	30	41	34	29	40	34	29	39	33	29	27																			

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P204846

CATALOG NUMBER: LE_6B60D010R EC6B60709730 6LBSCMW1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	236.9	3.9
10°-20°	674.3	11.0
20°-30°	1014.4	16.6
30°-40°	1202.2	19.6
40°-50°	1196.3	19.5
50°-60°	964.4	15.8
60°-70°	583.4	9.5
70°-80°	216.6	3.5
80°-90°	32.3	0.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1925.5	31.5
0°-40°	3127.7	51.1
0°-60°	5288.4	86.4
0°-90°	6120.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6120.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2500	
5°	2489	237
15°	2389	674
25°	2203	1014
35°	1925	1202
45°	1558	1196
55°	1076	964
65°	586	583
75°	197	217
85°	26	32
90°	0	



TEST NUMBER: P204846

CATALOG NUMBER: LE_6B60D010R EC6B60709730 6LBSCMW1

CANDELA DISTRIBUTION (FULL):

	0°
0°	2499.9
2.5°	2499.9
5°	2488.8
7.5°	2481.4
10°	2459.1
12.5°	2422.0
15°	2388.6
17.5°	2351.5
20°	2307.0
22.5°	2262.5
25°	2203.1
27.5°	2140.1
30°	2069.6
32.5°	2002.9
35°	1925.0
37.5°	1843.4
40°	1747.0
42.5°	1654.2
45°	1557.8
47.5°	1450.2
50°	1331.5
52.5°	1209.1
55°	1075.6
57.5°	956.9
60°	823.4
62.5°	704.8
65°	586.0
67.5°	474.8
70°	370.9
72.5°	278.1
75°	196.6
77.5°	126.1
80°	74.1
82.5°	44.5
85°	26.0
87.5°	11.1
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)