

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P203599

Luminaire Tested: **LE_6B60D010R EC6B60708040 6LBMMW1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P203599
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LE_6B60D010R EC6B60708040 6LBMMW1
Description: PORTFOLIO 6 INCH 50 DEGREE CUTOFF RECESSED DOWNLIGHT
MEDIUM DISTRIBUTION WITH MATTE WHITE TRIM
SINGLE DRIVER D010TE
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 6201.4 lumens
Efficiency: N/A
Efficacy: 99.2 lumens/watt
Spacing Criteria (0/90/45): 1 / 1 / 0.97
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 62.5
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P203599

CATALOG NUMBER: LE_6B60D010R EC6B60708040 6LBMMW1

Luminous Intensity Polar Plot





TEST NUMBER: P203599

CATALOG NUMBER: LE_6B60D010R EC6B60708040 6LBMMW1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10		0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	111	108	104	101	109	105	103	100	101	99	97	98	96	94	94	92	91	89		
2	104	97	92	88	101	96	91	87	92	88	85	89	86	83	86	83	81	79		
3	97	88	82	77	95	87	81	76	84	79	75	82	77	74	79	76	73	71		
4	90	81	74	68	88	80	73	68	77	72	67	75	70	66	73	69	65	64		
5	85	74	67	61	83	73	66	61	71	65	61	69	64	60	68	63	59	58		
6	79	68	61	56	78	68	61	56	66	60	55	64	59	55	63	58	54	53		
7	75	63	56	51	73	63	56	51	61	55	50	60	54	50	59	54	50	48		
8	70	59	52	47	69	58	51	47	57	51	46	56	50	46	55	50	46	44		
9	66	55	48	43	65	54	48	43	53	47	43	52	47	43	51	46	43	41		
10	63	51	45	40	62	51	44	40	50	44	40	49	44	40	48	43	40	38		

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P203599

CATALOG NUMBER: LE_6B60D010R EC6B60708040 6LBMMW1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	427.4	6.9
10°-20°	1144.9	18.5
20°-30°	1537.4	24.8
30°-40°	1261.0	20.3
40°-50°	757.3	12.2
50°-60°	503.3	8.1
60°-70°	337.3	5.4
70°-80°	181.5	2.9
80°-90°	51.2	0.8
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3109.7	50.1
0°-40°	4370.8	70.5
0°-60°	5631.4	90.8
0°-90°	6201.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6201.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	4627	
5°	4550	427
15°	4080	1145
25°	3387	1537
35°	2001	1261
45°	958	757
55°	556	503
65°	342	337
75°	171	182
85°	43	51
90°	0	



TEST NUMBER: P203599

CATALOG NUMBER: LE_6B60D010R EC6B60708040 6LBMMW1

CANDELA DISTRIBUTION (FULL):

	0°
0°	4627.2
2.5°	4593.0
5°	4550.2
7.5°	4456.1
10°	4345.0
12.5°	4208.1
15°	4079.9
17.5°	3925.9
20°	3771.9
22.5°	3600.9
25°	3387.0
27.5°	3130.5
30°	2788.4
32.5°	2403.4
35°	2001.4
37.5°	1659.2
40°	1368.5
42.5°	1137.6
45°	958.0
47.5°	812.5
50°	709.9
52.5°	624.4
55°	556.0
57.5°	496.1
60°	444.8
62.5°	384.9
65°	342.1
67.5°	290.8
70°	248.0
72.5°	205.2
75°	171.0
77.5°	136.9
80°	102.6
82.5°	77.0
85°	42.8
87.5°	17.1
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)