

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P203187

Luminaire Tested: **LE_6B60D010R EC6B60708040 6LBWMW1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P203187
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LE_6B60D010R EC6B60708040 6LBWMW1
Description: PORTFOLIO 6 INCH 60 DEGREE CUTOFF RECESSED DOWNLIGHT
WIDE DISTRIBUTION WITH MATTE WHITE TRIM
SINGLE DRIVER D010TE
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 7308.8 lumens
Efficiency: N/A
Efficacy: 116.9 lumens/watt
Spacing Criteria (0/90/45): 1.13 / 1.13 / 1.15
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 62.5
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P203187

CATALOG NUMBER: LE_6B60D010R EC6B60708040 6LBWMW1

Luminous Intensity Polar Plot





TEST NUMBER: P203187

CATALOG NUMBER: LE_6B60D010R EC6B60708040 6LBWMW1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	111	107	104	100	108	105	102	99	101	98	96	97	95	93	93	92	90	88			
2	103	96	90	86	100	94	89	85	91	86	83	88	84	81	85	82	79	77			
3	95	86	80	74	93	85	79	74	82	77	72	80	75	71	77	73	70	68			
4	89	78	71	65	86	77	70	65	75	69	64	72	67	63	70	66	62	60			
5	82	71	64	58	80	70	63	58	68	62	57	66	61	56	65	60	56	54			
6	77	65	57	52	75	64	57	52	63	56	51	61	55	51	60	54	50	49			
7	72	60	52	47	70	59	52	47	58	51	46	56	50	46	55	50	46	44			
8	67	55	48	42	66	55	47	42	53	47	42	52	46	42	51	46	42	40			
9	63	51	44	39	62	51	44	39	50	43	39	49	43	38	48	42	38	37			
10	60	48	40	36	58	47	40	36	46	40	36	45	40	35	45	39	35	34			

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P203187

CATALOG NUMBER: LE_6B60D010R EC6B60708040 6LBWMW1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	386.5	5.3
10°-20°	1084.0	14.8
20°-30°	1561.8	21.4
30°-40°	1621.6	22.2
40°-50°	1198.9	16.4
50°-60°	716.2	9.8
60°-70°	435.2	6.0
70°-80°	238.4	3.3
80°-90°	66.3	0.9
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3032.3	41.5
0°-40°	4653.9	63.7
0°-60°	6568.9	89.9
0°-90°	7308.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	7308.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	4104	
5°	4078	387
15°	3847	1084
25°	3404	1562
35°	2615	1622
45°	1542	1199
55°	780	716
65°	434	435
75°	222	238
85°	53	66
90°	0	



TEST NUMBER: P203187

CATALOG NUMBER: LE_6B60D010R EC6B60708040 6LBWMW1

CANDELA DISTRIBUTION (FULL):

0°	
0°	4104.4
2.5°	4104.4
5°	4077.8
7.5°	4042.2
10°	3989.1
12.5°	3927.0
15°	3847.2
17.5°	3758.6
20°	3670.0
22.5°	3545.9
25°	3404.0
27.5°	3253.4
30°	3058.2
32.5°	2863.2
35°	2615.1
37.5°	2358.0
40°	2074.4
42.5°	1799.5
45°	1542.5
47.5°	1312.0
50°	1108.1
52.5°	930.8
55°	780.1
57.5°	664.9
60°	567.4
62.5°	496.4
65°	434.4
67.5°	381.1
70°	328.0
72.5°	274.8
75°	221.6
77.5°	177.2
80°	133.0
82.5°	97.5
85°	53.2
87.5°	26.6
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)