

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P843942

Luminaire Tested: **LD6C10DE010B2750 EU6C10B27 6LBWH**

Issue Date: 2/17/2023

**Test Information**

Test Method: LM-79-08  
Report Number: P843942  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P202739)  
Test Lab: INNOVATION CENTER  
Issue Date: 2/17/2023  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: PORTFOLIO  
Catalog Number: LD6C10DE010B2750 EU6C10B27 6LBWH  
Description:  
Light Source: -  
Ballast/Driver:

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 1048.1 lumens  
Efficiency: N/A  
Efficacy: 78.8 lumens/watt  
Spacing Criteria (0/90/45): 1.16 / 1.16 / 1.16  
Luminous Opening: Circular (Dia: 0.5' x H: 0')  
CIE Type: Direct

Input Watts (W): 13.3  
Input Voltage (V):  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT

TEST NUMBER: P843942

CATALOG NUMBER: LD6C10DE010B2750 EU6C10B27 6LBWH

### Luminous Intensity Polar Plot





TEST NUMBER: P843942

CATALOG NUMBER: LD6C10DE010B2750 EU6C10B27 6LBWH

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			100
1	112	109	106	103	110	107	104	101	103	100	98	99	97	95	95	94	93	91			91
2	105	99	94	90	103	97	93	89	94	90	87	91	88	85	88	85	83	81			81
3	98	90	84	79	96	89	83	78	86	81	77	83	79	76	81	78	75	73			73
4	92	82	75	70	90	81	75	70	79	73	69	77	72	68	75	71	67	65			65
5	86	75	68	63	84	74	68	63	72	66	62	71	65	61	69	64	61	59			59
6	80	69	62	57	78	68	61	56	67	61	56	65	60	56	64	59	55	53			53
7	75	64	56	51	73	63	56	51	62	55	51	60	55	51	59	54	50	49			49
8	70	59	52	47	69	58	51	47	57	51	46	56	50	46	55	50	46	44			44
9	66	55	48	43	65	54	47	43	53	47	43	52	47	42	51	46	42	41			41
10	62	51	44	40	61	50	44	39	50	43	39	49	43	39	48	43	39	38			38

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	35436
5°	35428
10°	35153
15°	34915
20°	34385
25°	33601
30°	31631
35°	28630
40°	23909
45°	18320
50°	12972
55°	8181
60°	4616
65°	2996
70°	1955
75°	1440
80°	852
85°	881



TEST NUMBER: P843942

CATALOG NUMBER: LD6C10DE010B2750 EU6C10B27 6LBWH

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	61.1	5.8
10°-20°	173.2	16.5
20°-30°	254.0	24.2
30°-40°	264.4	25.2
40°-50°	182.9	17.5
50°-60°	79.6	7.6
60°-70°	24.4	2.3
70°-80°	7.3	0.7
80°-90°	1.1	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	488.3	46.6
0°-40°	752.7	71.8
0°-60°	1015.2	96.9
0°-90°	1048.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1048.1	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	646	
5°	644	61
15°	615	173
25°	556	254
35°	428	264
45°	236	183
55°	86	80
65°	23	24
75°	7	7
85°	1	1
90°	0	



TEST NUMBER: P843942

CATALOG NUMBER: LD6C10DE010B2750 EU6C10B27 6LBWH

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	646.4
2.5°	647.8
5°	643.8
7.5°	638.3
10°	631.5
12.5°	624.7
15°	615.2
17.5°	603.0
20°	589.4
22.5°	574.5
25°	555.5
27.5°	531.0
30°	499.7
32.5°	467.2
35°	427.8
37.5°	384.3
40°	334.1
42.5°	283.9
45°	236.3
47.5°	191.4
50°	152.1
52.5°	115.5
55°	85.6
57.5°	61.1
60°	42.1
62.5°	31.2
65°	23.1
67.5°	17.7
70°	12.2
72.5°	9.5
75°	6.8
77.5°	4.0
80°	2.7
82.5°	1.4
85°	1.4
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG







— 0°-180°







(END OF REPORT)