

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P844368

Luminaire Tested: **LD6C35DE010B2750 EU6C35B27 6LBWLI**

Issue Date: 2/17/2023



Test Information

Test Method: LM-79-08
Report Number: P844368
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P205209)
Test Lab: INNOVATION CENTER
Issue Date: 2/17/2023
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD6C35DE010B2750 EU6C35B27 6LBWLI
Description:
Light Source: -
Ballast/Driver:

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 4389.2 lumens
Efficiency: N/A
Efficacy: 105.3 lumens/watt
Spacing Criteria (0/90/45): 1.24 / 1.24 / 1.18
Luminous Opening: Circular (Dia: 0.5' x H: 0')
CIE Type: Direct

Input Watts (W): 41.7
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P844368

CATALOG NUMBER: LD6C35DE010B2750 EU6C35B27 6LBWLI

Luminous Intensity Polar Plot





TEST NUMBER: P844368

CATALOG NUMBER: LD6C35DE010B2750 EU6C35B27 6LBWLI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			100
1	113	110	107	104	110	107	105	103	103	101	99	100	98	97	96	95	94	92			92
2	106	101	96	92	104	99	95	91	95	92	89	92	90	87	90	87	85	83			83
3	100	92	87	82	97	91	86	81	88	84	80	86	82	79	83	80	77	76			76
4	93	85	78	73	92	84	78	73	81	76	72	79	75	71	77	74	70	69			69
5	88	78	71	66	86	77	71	66	75	70	65	73	69	65	72	68	64	63			63
6	82	72	65	60	81	71	65	60	70	64	59	68	63	59	67	62	59	57			57
7	77	67	60	55	76	66	59	55	65	59	54	63	58	54	62	57	54	52			52
8	73	62	55	50	71	61	55	50	60	54	50	59	54	50	58	53	49	48			48
9	69	57	51	46	67	57	50	46	56	50	46	55	50	46	54	49	46	44			44
10	65	54	47	43	64	53	47	42	52	46	42	51	46	42	51	46	42	41			41

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	150317
5°	151711
10°	155959
15°	159859
20°	162286
25°	158931
30°	149004
35°	133224
40°	107909
45°	71380
50°	36084
55°	15225
60°	4901
65°	1920
70°	1603
75°	1059
80°	0
85°	0



TEST NUMBER: P844368

CATALOG NUMBER: LD6C35DE010B2750 EU6C35B27 6LBWLI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	264.5	6.0
10°-20°	795.1	18.1
20°-30°	1198.5	27.3
30°-40°	1226.8	27.9
40°-50°	714.7	16.3
50°-60°	164.2	3.7
60°-70°	20.1	0.5
70°-80°	5.3	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2258.1	51.4
0°-40°	3484.9	79.4
0°-60°	4363.8	99.4
0°-90°	4389.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4389.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2742	
5°	2757	265
15°	2817	795
25°	2628	1199
35°	1991	1227
45°	921	715
55°	159	164
65°	15	20
75°	5	5
85°	0	0
90°	0	



TEST NUMBER: P844368

CATALOG NUMBER: LD6C35DE010B2750 EU6C35B27 6LBWLI

CANDELA DISTRIBUTION (FULL):

	0°
0°	2742.0
2.5°	2737.1
5°	2756.9
7.5°	2776.7
10°	2801.7
12.5°	2806.6
15°	2816.7
17.5°	2806.6
20°	2781.8
22.5°	2702.1
25°	2627.5
27.5°	2508.2
30°	2353.9
32.5°	2194.6
35°	1990.7
37.5°	1761.6
40°	1507.9
42.5°	1224.2
45°	920.7
47.5°	641.9
50°	423.1
52.5°	268.7
55°	159.3
57.5°	84.6
60°	44.7
62.5°	24.9
65°	14.8
67.5°	14.8
70°	10.0
72.5°	5.0
75°	5.0
77.5°	5.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)