

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P844380

Luminaire Tested: **LD6C35DE010B2750 EU6C35B30 6LBNH**

Issue Date: 2/17/2023

Test Information

Test Method: LM-79-08
Report Number: P844380
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P203666)
Test Lab: INNOVATION CENTER
Issue Date: 2/17/2023
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD6C35DE010B2750 EU6C35B30 6LBNH
Description:
Light Source: -
Ballast/Driver:

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2692.7 lumens
Efficiency: N/A
Efficacy: 64.6 lumens/watt
Spacing Criteria (0/90/45): 0.78 / 0.78 / 0.84
Luminous Opening: Circular (Dia: 0.5' x H: 0')
CIE Type: Direct

Input Watts (W): 41.7
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P844380

CATALOG NUMBER: LD6C35DE010B2750 EU6C35B30 6LBNH

Luminous Intensity Polar Plot





TEST NUMBER: P844380

CATALOG NUMBER: LD6C35DE010B2750 EU6C35B30 6LBNH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	113	111	108	106	111	109	106	104	104	103	101	101	99	98	97	96	95	93			
2	108	103	99	96	106	101	98	94	98	95	92	95	93	90	92	90	89	87			
3	102	96	91	87	100	95	90	86	92	88	85	90	86	84	87	85	82	81			
4	97	90	84	80	95	89	83	79	86	82	78	84	81	78	83	79	77	75			
5	92	84	78	74	91	83	78	73	81	76	73	80	75	72	78	74	72	70			
6	88	79	73	69	86	78	72	68	77	72	68	75	71	67	74	70	67	65			
7	83	74	68	64	82	73	68	64	72	67	63	71	66	63	70	66	63	61			
8	79	70	64	60	78	69	64	60	68	63	59	67	63	59	66	62	59	58			
9	76	66	60	56	75	66	60	56	65	59	56	64	59	56	63	59	55	54			
10	72	62	57	53	71	62	57	53	61	56	53	60	56	52	60	55	52	51			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	189228
5°	184542
10°	170282
15°	150761
20°	130906
25°	111968
30°	92312
35°	60786
40°	32676
45°	14467
50°	5859
55°	4234
60°	2686
65°	1920
70°	1571
75°	1059
80°	1578
85°	0



TEST NUMBER: P844380

CATALOG NUMBER: LD6C35DE010B2750 EU6C35B30 6LBNH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	310.4	11.5
10°-20°	740.2	27.5
20°-30°	848.0	31.5
30°-40°	569.7	21.2
40°-50°	162.8	6.0
50°-60°	39.8	1.5
60°-70°	15.1	0.6
70°-80°	5.9	0.2
80°-90°	0.7	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1898.7	70.5
0°-40°	2468.4	91.7
0°-60°	2671.0	99.2
0°-90°	2692.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2692.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3452	
5°	3354	310
15°	2656	740
25°	1851	848
35°	908	570
45°	187	163
55°	44	40
65°	15	15
75°	5	6
85°	0	1
90°	0	



TEST NUMBER: P844380

CATALOG NUMBER: LD6C35DE010B2750 EU6C35B30 6LBNH

CANDELA DISTRIBUTION (FULL):

	0°
0°	3451.8
2.5°	3427.3
5°	3353.5
7.5°	3220.9
10°	3059.0
12.5°	2852.6
15°	2656.4
17.5°	2450.2
20°	2243.9
22.5°	2047.5
25°	1851.1
27.5°	1669.4
30°	1458.3
32.5°	1178.3
35°	908.3
37.5°	662.8
40°	456.6
42.5°	299.5
45°	186.6
47.5°	112.8
50°	68.7
52.5°	53.9
55°	44.3
57.5°	34.4
60°	24.5
62.5°	19.6
65°	14.8
67.5°	9.8
70°	9.8
72.5°	5.0
75°	5.0
77.5°	5.0
80°	5.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)