

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P843905

Luminaire Tested: **LD6C08DE010B2750 EU6C08B40 6LBNLI**

Issue Date: 2/17/2023



Test Information

Test Method: LM-79-08
Report Number: P843905
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P205310)
Test Lab: INNOVATION CENTER
Issue Date: 2/17/2023
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD6C08DE010B2750 EU6C08B40 6LBNLI
Description:
Light Source: -
Ballast/Driver:

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 663.2 lumens
Efficiency: N/A
Efficacy: 69.1 lumens/watt
Spacing Criteria (0/90/45): 0.53 / 0.53 / 0.58
Luminous Opening: Circular (Dia: 0.5' x H: 0')
CIE Type: Direct

Input Watts (W): 9.6
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P843905

CATALOG NUMBER: LD6C08DE010B2750 EU6C08B40 6LBNLI

Luminous Intensity Polar Plot





TEST NUMBER: P843905

CATALOG NUMBER: LD6C08DE010B2750 EU6C08B40 6LBNLI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20
RC	80					70					50					30					0
RW	70	50	30	10		70	50	30	10		50	30	10			50	30	10			0
RCR																					
0	119	119	119	119		116	116	116	116		111	111	111			106	106	106			100
1	114	112	109	107		112	109	107	106		105	104	102			102	101	99			95
2	109	105	101	98		107	103	100	97		100	97	95			97	95	93			89
3	105	99	94	91		103	97	93	90		95	91	89			93	90	87			85
4	100	93	88	85		98	92	88	84		90	86	83			88	85	82			80
5	96	88	83	79		94	87	83	79		86	82	78			84	81	78			76
6	92	84	79	75		90	83	78	75		82	77	74			80	76	74			72
7	88	80	74	71		87	79	74	71		78	73	70			77	73	70			68
8	84	76	71	67		83	75	70	67		74	70	67			73	69	66			65
9	81	73	67	64		80	72	67	64		71	67	63			70	66	63			62
10	78	69	64	61		77	69	64	61		68	64	61			67	63	60			59

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	82767
5°	77399
10°	63125
15°	46453
20°	32016
25°	23772
30°	17857
35°	11136
40°	5403
45°	1853
50°	247
55°	182
60°	110
65°	130
70°	160
75°	0
80°	0
85°	0



TEST NUMBER: P843905

CATALOG NUMBER: LD6C08DE010B2750 EU6C08B40 6LBNLI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	125.5	18.9
10°-20°	225.3	34.0
20°-30°	182.2	27.5
30°-40°	105.0	15.8
40°-50°	22.2	3.3
50°-60°	1.9	0.3
60°-70°	1.0	0.1
70°-80°	0.1	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	533.0	80.4
0°-40°	638.0	96.2
0°-60°	662.1	99.8
0°-90°	663.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	663.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1510	
5°	1406	126
15°	818	225
25°	393	182
35°	166	105
45°	24	22
55°	2	2
65°	1	1
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P843905

CATALOG NUMBER: LD6C08DE010B2750 EU6C08B40 6LBNLI

CANDELA DISTRIBUTION (FULL):

0°	
0°	1509.8
2.5°	1491.7
5°	1406.5
7.5°	1284.2
10°	1134.0
12.5°	980.1
15°	818.5
17.5°	662.6
20°	548.8
22.5°	461.9
25°	393.0
27.5°	334.6
30°	282.1
32.5°	223.8
35°	166.4
37.5°	115.7
40°	75.5
42.5°	45.9
45°	23.9
47.5°	9.5
50°	2.9
52.5°	2.9
55°	1.9
57.5°	1.9
60°	1.0
62.5°	1.0
65°	1.0
67.5°	1.0
70°	1.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)