

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P245310

Luminaire Tested: **LSR8B10D010 EC8B10827 8LBS0WH**

Issue Date: 03/03/2020

**Test Information**

Test Method: LM-79-08  
Report Number: P245310  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-1801-521-15)  
Test Lab: INNOVATION CENTER(G1)  
Issue Date: 03/03/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: PORTFOLIO  
Catalog Number: LSR8B10D010 EC8B10827 8LBS0WH  
Description: PORTFOLIO 8 INCH WIDE SHALLOW DISTRIBUTION 75 DEGREE CUTOFF RECESSED  
DOWNLIGHT- CYLINDEC  
80 CRI 2700 CCT WITH WHEAT TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 1137.0 lumens  
Efficiency: N/A  
Efficacy: 111.5 lumens/watt  
Spacing Criteria (0/90/45): 1.27 / 1.27 / 1.23  
Luminous Opening: Circular (Dia: 0.67' x H: 0')  
CIE Type: Direct


Input Watts (W): 10.2  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P245310

CATALOG NUMBER: LSR8B10D010 EC8B10827 8LBS0WH

### Luminous Intensity Polar Plot





TEST NUMBER: P245310

CATALOG NUMBER: LSR8B10D010 EC8B10827 8LBS0WH

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	112	109	106	104	110	107	104	102	103	101	99	99	97	96	96	94	93	91
2	105	100	95	91	103	98	93	90	94	91	88	91	88	86	89	86	84	82
3	99	91	85	80	96	89	84	79	87	82	78	84	80	77	82	78	76	74
4	92	83	76	71	90	82	76	71	79	74	70	77	73	69	75	71	68	66
5	86	76	69	64	84	75	68	63	73	67	63	71	66	62	70	65	62	60
6	80	70	63	57	79	69	62	57	67	61	57	66	60	56	64	60	56	54
7	75	64	57	52	74	63	57	52	62	56	51	61	55	51	60	55	51	49
8	71	59	52	47	69	59	52	47	57	51	47	56	51	47	55	50	46	45
9	66	55	48	43	65	54	48	43	53	47	43	52	47	43	51	46	43	41
10	63	51	44	40	61	51	44	40	50	44	39	49	43	39	48	43	39	38

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	19859
5°	19934
10°	20187
15°	20581
20°	20874
25°	20959
30°	20317
35°	18544
40°	16041
45°	12629
50°	8146
55°	4000
60°	1647
65°	722
70°	207
75°	83
80°	53
85°	0



TEST NUMBER: P245310

CATALOG NUMBER: LSR8B10D010 EC8B10827 8LBS0WH

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	61.5	5.4
10°-20°	182.2	16.0
20°-30°	282.1	24.8
30°-40°	305.6	26.9
40°-50°	219.9	19.3
50°-60°	73.6	6.5
60°-70°	11.1	1.0
70°-80°	1.0	0.1
80°-90°	0.1	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	525.7	46.2
0°-40°	831.3	73.1
0°-60°	1124.8	98.9
0°-90°	1137.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1137.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	644	
5°	644	61
15°	645	182
25°	616	282
35°	493	306
45°	290	220
55°	74	74
65°	10	11
75°	1	1
85°	0	0
90°	0	



TEST NUMBER: P245310

CATALOG NUMBER: LSR8B10D010 EC8B10827 8LBS0WH

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	644.0
2.5°	644.0
5°	644.0
7.5°	644.3
10°	644.7
12.5°	645.3
15°	644.7
17.5°	642.0
20°	636.1
22.5°	627.2
25°	616.0
27.5°	598.3
30°	570.6
32.5°	534.4
35°	492.6
37.5°	447.5
40°	398.5
42.5°	345.9
45°	289.6
47.5°	228.7
50°	169.8
52.5°	116.5
55°	74.4
57.5°	44.4
60°	26.7
62.5°	16.1
65°	9.9
67.5°	4.9
70°	2.3
72.5°	1.0
75°	0.7
77.5°	0.7
80°	0.3
82.5°	0.3
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)