

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P246621

Luminaire Tested: **LSR8B30D010 EC8B30835 8LBN0MW**

Issue Date: 03/03/2020

Test Information

Test Method: LM-79-08
Report Number: P246621
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P201839)
Test Lab: INNOVATION CENTER-P1
Issue Date: 03/03/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LSR8B30D010 EC8B30835 8LBN0MW
Description: PORTFOLIO 8 INCH NARROW DISTRIBUTION 50 DEGREE CUTOFF RECESSED
DOWNLIGHT- CYLINDEC
80 CRI 3500 CCT WITH MATTE WHITE TRIM
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2849.0 lumens
Efficiency: N/A
Efficacy: 105.1 lumens/watt
Spacing Criteria (0/90/45): 0.79 / 0.79 / 0.85
Luminous Opening: Circular (Dia: 0.67' x H: 0')
CIE Type: Direct


Input Watts (W): 27.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P246621

CATALOG NUMBER: LSR8B30D010 EC8B30835 8LBN0MW

Luminous Intensity Polar Plot





TEST NUMBER: P246621

CATALOG NUMBER: LSR8B30D010 EC8B30835 8LBN0MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	112	109	106	103	109	106	104	101	102	100	98		98	97	95		95	94	92	90
2	105	99	94	90	103	97	93	89	94	90	87		91	88	85		88	86	83	82
3	99	91	85	80	96	89	84	79	87	82	78		84	80	77		82	78	76	74
4	93	84	77	72	91	83	76	72	80	75	71		78	74	70		76	72	69	67
5	87	78	71	66	85	77	70	65	75	69	65		73	68	64		71	67	64	62
6	82	72	65	60	81	71	65	60	70	64	60		68	63	59		67	62	59	57
7	78	67	60	56	76	67	60	55	65	59	55		64	59	55		63	58	54	53
8	74	63	56	52	72	62	56	51	61	55	51		60	55	51		59	54	51	49
9	70	59	53	48	69	59	52	48	58	52	48		57	51	48		56	51	47	46
10	66	56	49	45	65	55	49	45	54	49	45		54	48	45		53	48	45	43

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	92130
5°	91469
10°	83356
15°	71446
20°	63320
25°	56504
30°	45630
35°	31663
40°	20087
45°	14923
50°	12737
55°	11166
60°	9991
65°	8931
70°	7691
75°	7077
80°	6588
85°	5802



TEST NUMBER: P246621

CATALOG NUMBER: LSR8B30D010 EC8B30835 8LBN0MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	272.6	9.6
10°-20°	630.4	22.1
20°-30°	749.7	26.3
30°-40°	530.0	18.6
40°-50°	273.6	9.6
50°-60°	187.6	6.6
60°-70°	121.7	4.3
70°-80°	63.8	2.2
80°-90°	19.6	0.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1652.7	58.0
0°-40°	2182.7	76.6
0°-60°	2643.8	92.8
0°-90°	2849.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2849.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2988	
5°	2955	273
15°	2238	630
25°	1661	750
35°	841	530
45°	342	274
55°	208	188
65°	122	122
75°	59	64
85°	16	18
90°	0	1
95°	0	0
105°	0	0
115°	0	0
125°	0	0
135°	0	0
145°	0	0
155°	0	0
165°	0	0
175°	0	0
180°	0	0



TEST NUMBER: P246621

CATALOG NUMBER: LSR8B30D010 EC8B30835 8LBN0MW

CANDELA DISTRIBUTION (FULL):

0°	
0°	2987.7
2.5°	2987.7
5°	2955.0
7.5°	2846.4
10°	2662.1
12.5°	2442.2
15°	2238.0
17.5°	2070.0
20°	1929.6
22.5°	1796.8
25°	1660.7
27.5°	1489.9
30°	1281.5
32.5°	1057.4
35°	841.1
37.5°	648.0
40°	499.0
42.5°	401.6
45°	342.2
47.5°	299.1
50°	265.5
52.5°	236.1
55°	207.7
57.5°	182.7
60°	162.0
62.5°	140.4
65°	122.4
67.5°	106.0
70°	85.3
72.5°	73.3
75°	59.4
77.5°	48.2
80°	37.1
82.5°	27.6
85°	16.4
87.5°	9.5
90°	0.0
92.5°	0.0
95°	0.0
97.5°	0.0
100°	0.0
102.5°	0.0
105°	0.0
107.5°	0.0
110°	0.0



TEST NUMBER: P246621

CATALOG NUMBER: LSR8B30D010 EC8B30835 8LBN0MW

CANDELA DISTRIBUTION (continued):

	0°
112.5°	0.0
115°	0.0
117.5°	0.0
120°	0.0
122.5°	0.0
125°	0.0
127.5°	0.0
130°	0.0
132.5°	0.0
135°	0.0
137.5°	0.0
140°	0.0
142.5°	0.0
145°	0.0
147.5°	0.0
150°	0.0
152.5°	0.0
155°	0.0
157.5°	0.0
160°	0.0
162.5°	0.0
165°	0.0
167.5°	0.0
170°	0.0
172.5°	0.0
175°	0.0
177.5°	0.0
180°	0.0

(END OF REPORT)