

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P245715

Luminaire Tested: **LSR8B30D010 EC8B30935 8LBM0GPH**

Issue Date: 03/03/2020

Test Information

Test Method: LM-79-08
Report Number: P245715
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P201629)
Test Lab: INNOVATION CENTER-P1
Issue Date: 03/03/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LSR8B30D010 EC8B30935 8LBM0GPH
Description: PORTFOLIO 8 INCH MEDIUM DISTRIBUTION 55 DEG CUTOFF RECESSED
DOWNLIGHT- CYLINDEC
90 CRI 3500 CCT WITH GRAPHITE TRIM
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2322.0 lumens
Efficiency: N/A
Efficacy: 85.7 lumens/watt
Spacing Criteria (0/90/45): 0.82 / 0.82 / 0.87
Luminous Opening: Circular (Dia: 0.67' x H: 0')
CIE Type: Direct


Input Watts (W): 27.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P245715

CATALOG NUMBER: LSR8B30D010 EC8B30935 8LBM0GPH

Luminous Intensity Polar Plot





TEST NUMBER: P245715

CATALOG NUMBER: LSR8B30D010 EC8B30935 8LBM0GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	114	111	108	106	111	109	107	105	105	103	101		101	100	98		98	96	95	94
2	108	103	99	96	106	102	98	95	98	95	93		95	93	91		93	91	89	87
3	103	96	92	88	101	95	91	87	92	89	86		90	87	84		88	85	83	81
4	98	90	85	81	96	89	84	80	87	83	79		85	81	78		83	80	77	76
5	93	85	79	75	91	84	78	74	82	77	74		80	76	73		79	75	72	71
6	88	79	73	69	87	79	73	69	77	72	69		76	71	68		74	71	68	66
7	84	75	69	65	82	74	68	64	73	68	64		72	67	64		70	66	63	62
8	80	70	64	60	79	70	64	60	69	64	60		68	63	60		67	63	59	58
9	76	66	61	57	75	66	60	57	65	60	56		64	59	56		63	59	56	55
10	72	63	57	53	71	62	57	53	62	57	53		61	56	53		60	56	53	51

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	90825
5°	88519
10°	79373
15°	70677
20°	64489
25°	58562
30°	48030
35°	31625
40°	15759
45°	5861
50°	1785
55°	199
60°	123
65°	0
70°	81
75°	346
80°	0
85°	318



TEST NUMBER: P245715

CATALOG NUMBER: LSR8B30D010 EC8B30935 8LBM0GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	262.2	11.3
10°-20°	623.4	26.8
20°-30°	776.5	33.4
30°-40°	524.0	22.6
40°-50°	123.9	5.3
50°-60°	9.0	0.4
60°-70°	1.6	0.1
70°-80°	1.1	0.0
80°-90°	0.2	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1662.2	71.6
0°-40°	2186.2	94.2
0°-60°	2319.0	99.9
0°-90°	2322.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2322.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2945	
5°	2860	262
15°	2214	623
25°	1721	777
35°	840	524
45°	134	124
55°	4	9
65°	0	2
75°	3	1
85°	1	0
90°	0	0
95°	0	0
105°	0	0
115°	0	0
125°	0	0
135°	0	0
145°	0	0
155°	0	0
165°	0	0
175°	0	0
180°	0	0



TEST NUMBER: P245715

CATALOG NUMBER: LSR8B30D010 EC8B30935 8LBM0GPH

CANDELA DISTRIBUTION (FULL):

0°	
0°	2945.4
2.5°	2940.7
5°	2859.7
7.5°	2713.9
10°	2534.9
12.5°	2364.4
15°	2213.9
17.5°	2084.2
20°	1965.2
22.5°	1849.9
25°	1721.2
27.5°	1553.6
30°	1348.9
32.5°	1101.2
35°	840.1
37.5°	601.2
40°	391.5
42.5°	234.3
45°	134.4
47.5°	75.3
50°	37.2
52.5°	17.1
55°	3.7
57.5°	0.9
60°	2.0
62.5°	2.9
65°	0.0
67.5°	2.0
70°	0.9
72.5°	0.9
75°	2.9
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.9
87.5°	0.0
90°	0.0
92.5°	0.0
95°	0.0
97.5°	0.0
100°	0.0
102.5°	0.0
105°	0.0
107.5°	0.0
110°	0.0



TEST NUMBER: P245715

CATALOG NUMBER: LSR8B30D010 EC8B30935 8LBM0GPH

CANDELA DISTRIBUTION (continued):

	0°
112.5°	0.0
115°	0.0
117.5°	0.0
120°	0.0
122.5°	0.0
125°	0.0
127.5°	0.0
130°	0.0
132.5°	0.0
135°	0.0
137.5°	0.0
140°	0.0
142.5°	0.0
145°	0.0
147.5°	0.0
150°	0.0
152.5°	0.0
155°	0.0
157.5°	0.0
160°	0.0
162.5°	0.0
165°	0.0
167.5°	0.0
170°	0.0
172.5°	0.0
175°	0.0
177.5°	0.0
180°	0.0

(END OF REPORT)