

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P245367

Luminaire Tested: **LSR8B30D010 EC8B30950 8LBS0WH**

Issue Date: 03/03/2020

**Test Information**

Test Method: LM-79-08  
Report Number: P245367  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-1801-521-15)  
Test Lab: INNOVATION CENTER(G1)  
Issue Date: 03/03/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: PORTFOLIO  
Catalog Number: LSR8B30D010 EC8B30950 8LBS0WH  
Description: PORTFOLIO 8 INCH WIDE SHALLOW DISTRIBUTION 75 DEGREE CUTOFF RECESSED  
DOWNLIGHT- CYLINDEC  
90 CRI 5000 CCT WITH WHEAT TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 3186.0 lumens  
Efficiency: N/A  
Efficacy: 117.6 lumens/watt  
Spacing Criteria (0/90/45): 1.27 / 1.27 / 1.23  
Luminous Opening: Circular (Dia: 0.67' x H: 0')  
CIE Type: Direct


Input Watts (W): 27.1  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P245367

CATALOG NUMBER: LSR8B30D010 EC8B30950 8LBS0WH

### Luminous Intensity Polar Plot





TEST NUMBER: P245367

CATALOG NUMBER: LSR8B30D010 EC8B30950 8LBS0WH

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	112	109	106	104	110	107	104	102	103	101	99	99	97	96	96	94	93	91
2	105	100	95	91	103	98	93	90	94	91	88	91	88	86	89	86	84	82
3	99	91	85	80	96	89	84	79	87	82	78	84	80	77	82	78	76	74
4	92	83	76	71	90	82	76	71	79	74	70	77	73	69	75	71	68	66
5	86	76	69	64	84	75	68	63	73	67	63	71	66	62	70	65	62	60
6	80	70	63	57	79	69	62	57	67	61	57	66	60	56	64	60	56	54
7	75	64	57	52	74	63	57	52	62	56	51	61	55	51	60	55	51	49
8	71	59	52	47	69	59	52	47	57	51	47	56	51	47	55	50	46	45
9	66	55	48	43	65	54	48	43	53	47	43	52	47	43	51	46	43	41
10	63	51	44	40	61	51	44	40	50	44	39	49	43	39	48	43	39	38

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	55647
5°	55860
10°	56562
15°	57668
20°	58493
25°	58732
30°	56935
35°	51964
40°	44952
45°	35389
50°	22825
55°	11204
60°	4607
65°	2021
70°	586
75°	214
80°	160
85°	0



TEST NUMBER: P245367

CATALOG NUMBER: LSR8B30D010 EC8B30950 8LBS0WH

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	172.3	5.4
10°-20°	510.5	16.0
20°-30°	790.4	24.8
30°-40°	856.3	26.9
40°-50°	616.2	19.3
50°-60°	206.1	6.5
60°-70°	31.2	1.0
70°-80°	2.7	0.1
80°-90°	0.4	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1473.2	46.2
0°-40°	2329.5	73.1
0°-60°	3151.8	98.9
0°-90°	3186.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3186.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	1805	
5°	1805	172
15°	1806	511
25°	1726	790
35°	1380	856
45°	812	616
55°	208	206
65°	28	31
75°	2	3
85°	0	0
90°	0	



TEST NUMBER: P245367

CATALOG NUMBER: LSR8B30D010 EC8B30950 8LBS0WH

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	1804.6
2.5°	1804.6
5°	1804.6
7.5°	1805.5
10°	1806.4
12.5°	1808.3
15°	1806.4
17.5°	1799.1
20°	1782.5
22.5°	1757.6
25°	1726.2
27.5°	1676.4
30°	1599.0
32.5°	1497.5
35°	1380.4
37.5°	1254.1
40°	1116.7
42.5°	969.1
45°	811.5
47.5°	640.9
50°	475.8
52.5°	326.4
55°	208.4
57.5°	124.5
60°	74.7
62.5°	45.2
65°	27.7
67.5°	13.8
70°	6.5
72.5°	2.8
75°	1.8
77.5°	1.8
80°	0.9
82.5°	0.9
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)