

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P245595

Luminaire Tested: **LSR8B30D010 EC8B309730 8LBW0GPH**

Issue Date: 03/03/2020

**Test Information**

Test Method: LM-79-08  
Report Number: P245595  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-1801-521-46)  
Test Lab: INNOVATION CENTER(G1)  
Issue Date: 03/03/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: PORTFOLIO  
Catalog Number: LSR8B30D010 EC8B309730 8LBW0GPH  
Description: PORTFOLIO 8 INCH WIDE DISTRIBUTION 60 DEGREE CUTOFF RECESSED  
DOWNLIGHT- CYLINDEC  
97 CRI 3000 CCT WITH GRAPHITE TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 2041.0 lumens  
Efficiency: N/A  
Efficacy: 75.3 lumens/watt  
Spacing Criteria (0/90/45): 1.11 / 1.11 / 1.05  
Luminous Opening: Point Source (0' x 0' x 0')  
CIE Type: Direct


Input Watts (W): 27.1  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P245595

CATALOG NUMBER: LSR8B30D010 EC8B309730 8LBW0GPH

### Luminous Intensity Polar Plot





TEST NUMBER: P245595

CATALOG NUMBER: LSR8B30D010 EC8B309730 8LBW0GPH

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	113	110	107	104	110	108	105	103	103	101	100	100	98	97	96	95	94	92
2	106	101	96	92	104	99	95	91	96	92	89	93	90	87	90	88	86	84
3	100	93	87	83	98	91	86	82	89	84	81	86	82	79	84	81	78	76
4	94	85	79	74	92	84	78	74	82	77	73	80	76	72	78	74	71	70
5	88	79	72	67	87	78	72	67	76	71	66	74	70	66	73	69	65	64
6	83	73	66	61	82	72	66	61	71	65	61	69	64	60	68	63	60	58
7	78	68	61	56	77	67	61	56	66	60	56	65	59	56	63	59	55	54
8	74	63	56	52	73	63	56	52	61	56	51	60	55	51	59	55	51	49
9	70	59	52	48	69	58	52	48	57	52	48	57	51	47	56	51	47	46
10	66	55	49	44	65	55	49	44	54	48	44	53	48	44	52	47	44	43

**AVERAGE LUMINANCE (cd/sqm):**





TEST NUMBER: P245595

CATALOG NUMBER: LSR8B30D010 EC8B309730 8LBW0GPH

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	145.4	7.1
10°-20°	403.8	19.8
20°-30°	593.0	29.1
30°-40°	537.5	26.3
40°-50°	230.1	11.3
50°-60°	101.8	5.0
60°-70°	27.2	1.3
70°-80°	2.1	0.1
80°-90°	0.1	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1142.2	56.0
0°-40°	1679.7	82.3
0°-60°	2011.6	98.6
0°-90°	2041.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2041.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	1589	
5°	1546	145
15°	1431	404
25°	1298	593
35°	897	538
45°	278	230
55°	110	102
65°	25	27
75°	2	2
85°	0	0
90°	0	



TEST NUMBER: P245595

CATALOG NUMBER: LSR8B30D010 EC8B309730 8LBW0GPH

**CANDELA DISTRIBUTION (FULL):**

0°	
0°	1589.2
2.5°	1576.7
5°	1545.8
7.5°	1510.4
10°	1480.2
12.5°	1455.1
15°	1430.8
17.5°	1405.0
20°	1375.6
22.5°	1340.9
25°	1298.2
27.5°	1240.7
30°	1161.9
32.5°	1051.4
35°	897.4
37.5°	695.5
40°	501.0
42.5°	361.8
45°	277.8
47.5°	224.0
50°	182.0
52.5°	144.4
55°	110.5
57.5°	82.5
60°	60.4
62.5°	42.0
65°	25.1
67.5°	11.1
70°	5.2
72.5°	2.9
75°	1.5
77.5°	0.7
80°	0.7
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)