

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P251270

Luminaire Tested: **LSR8B60D010 EC8B60850 8LBM0GPH**

Issue Date: 03/03/2020

**Test Information**

Test Method: LM-79-08  
Report Number: P251270  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P201629)  
Test Lab: INNOVATION CENTER-P1  
Issue Date: 03/03/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: PORTFOLIO  
Catalog Number: LSR8B60D010 EC8B60850 8LBM0GPH  
Description: PORTFOLIO 8 INCH MEDIUM DISTRIBUTION 55 DEG CUTOFF RECESSED  
DOWNLIGHT- CYLINDEC  
80 CRI 5000 CCT WITH GRAPHITE TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 5562.0 lumens  
Efficiency: N/A  
Efficacy: 93.5 lumens/watt  
Spacing Criteria (0/90/45): 0.82 / 0.82 / 0.87  
Luminous Opening: Circular (Dia: 0.67' x H: 0')  
CIE Type: Direct


Input Watts (W): 59.5  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P251270

CATALOG NUMBER: LSR8B60D010 EC8B60850 8LBM0GPH

### Luminous Intensity Polar Plot





TEST NUMBER: P251270

CATALOG NUMBER: LSR8B60D010 EC8B60850 8LBM0GPH

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	114	111	108	106	111	109	107	105	105	103	101		101	100	98		98	96	95	94
2	108	103	99	96	106	102	98	95	98	95	93		95	93	91		93	91	89	87
3	103	96	92	88	101	95	91	87	92	89	86		90	87	84		88	85	83	81
4	98	90	85	81	96	89	84	80	87	83	79		85	81	78		83	80	77	76
5	93	85	79	75	91	84	78	74	82	77	74		80	76	73		79	75	72	71
6	88	79	73	69	87	79	73	69	77	72	69		76	71	68		74	71	68	66
7	84	75	69	65	82	74	68	64	73	68	64		72	67	64		70	66	63	62
8	80	70	64	60	79	70	64	60	69	64	60		68	63	60		67	63	59	58
9	76	66	61	57	75	66	60	57	65	60	56		64	59	56		63	59	56	55
10	72	63	57	53	71	62	57	53	62	57	53		61	56	53		60	56	53	51

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	217556
5°	212036
10°	190123
15°	169294
20°	154472
25°	140281
30°	115045
35°	75755
40°	37750
45°	14038
50°	4274
55°	484
60°	290
65°	0
70°	198
75°	834
80°	0
85°	778



TEST NUMBER: P251270

CATALOG NUMBER: LSR8B60D010 EC8B60850 8LBM0GPH

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	628.1	11.3
10°-20°	1493.3	26.8
20°-30°	1860.1	33.4
30°-40°	1255.2	22.6
40°-50°	296.7	5.3
50°-60°	21.5	0.4
60°-70°	3.7	0.1
70°-80°	2.7	0.0
80°-90°	0.6	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3981.5	71.6
0°-40°	5236.8	94.2
0°-60°	5554.9	99.9
0°-90°	5562.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5562.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	7055	
5°	6850	628
15°	5303	1493
25°	4123	1860
35°	2012	1255
45°	322	297
55°	9	22
65°	0	4
75°	7	3
85°	2	1
90°	0	0
95°	0	0
105°	0	0
115°	0	0
125°	0	0
135°	0	0
145°	0	0
155°	0	0
165°	0	0
175°	0	0
180°	0	0



TEST NUMBER: P251270

CATALOG NUMBER: LSR8B60D010 EC8B60850 8LBM0GPH

**CANDELA DISTRIBUTION (FULL):**

0°	
0°	7055.2
2.5°	7044.0
5°	6850.0
7.5°	6500.8
10°	6071.9
12.5°	5663.5
15°	5303.0
17.5°	4992.4
20°	4707.3
22.5°	4431.2
25°	4123.0
27.5°	3721.5
30°	3231.0
32.5°	2637.7
35°	2012.4
37.5°	1440.0
40°	937.8
42.5°	561.2
45°	321.9
47.5°	180.3
50°	89.1
52.5°	41.0
55°	9.0
57.5°	2.2
60°	4.7
62.5°	7.0
65°	0.0
67.5°	4.7
70°	2.2
72.5°	2.2
75°	7.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	2.2
87.5°	0.0
90°	0.0
92.5°	0.0
95°	0.0
97.5°	0.0
100°	0.0
102.5°	0.0
105°	0.0
107.5°	0.0
110°	0.0



TEST NUMBER: P251270

CATALOG NUMBER: LSR8B60D010 EC8B60850 8LBM0GPH

**CANDELA DISTRIBUTION (continued):**

	0°
112.5°	0.0
115°	0.0
117.5°	0.0
120°	0.0
122.5°	0.0
125°	0.0
127.5°	0.0
130°	0.0
132.5°	0.0
135°	0.0
137.5°	0.0
140°	0.0
142.5°	0.0
145°	0.0
147.5°	0.0
150°	0.0
152.5°	0.0
155°	0.0
157.5°	0.0
160°	0.0
162.5°	0.0
165°	0.0
167.5°	0.0
170°	0.0
172.5°	0.0
175°	0.0
177.5°	0.0
180°	0.0

(END OF REPORT)