

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P246988

Luminaire Tested: **LSR8B100D010 EC8B100950 8LBM0LI**

Issue Date: 03/03/2020

**Test Information**

Test Method: LM-79-08  
Report Number: P246988  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-1801-521-81)  
Test Lab: INNOVATION CENTER(G1)  
Issue Date: 03/03/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: PORTFOLIO  
Catalog Number: LSR8B100D010 EC8B100950 8LBMOLI  
Description: PORTFOLIO 8 INCH MEDIUM DISTRIBUTION 55 DEG CUTOFF RECESSED  
DOWNLIGHT- CYLINDEC  
90 CRI 5000 CCT WITH SPECULAR CLEAR TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 10308.0 lumens  
Efficiency: N/A  
Efficacy: 97.0 lumens/watt  
Spacing Criteria (0/90/45): 0.67 / 0.67 / 0.75  
Luminous Opening: Circular (Dia: 0.67' x H: 0')  
CIE Type: Direct


Input Watts (W): 106.3  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P246988

CATALOG NUMBER: LSR8B100D010 EC8B100950 8LBM0LI

### Luminous Intensity Polar Plot





TEST NUMBER: P246988

CATALOG NUMBER: LSR8B100D010 EC8B100950 8LBM0LI

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	114	111	109	107	111	109	107	105	105	103	102	101	100	99	98	97	96	94
2	109	104	100	97	107	102	99	96	99	96	94	96	94	92	94	92	90	88
3	104	98	93	89	102	96	92	89	94	90	87	91	88	86	89	87	85	83
4	99	92	87	83	97	91	86	82	89	85	81	87	83	80	85	82	79	78
5	94	87	81	77	93	86	81	77	84	79	76	82	78	75	81	77	75	73
6	90	82	76	72	89	81	76	72	79	75	71	78	74	71	77	73	70	69
7	86	77	72	68	85	77	71	68	75	71	67	74	70	67	73	69	67	65
8	82	73	68	64	81	73	67	64	72	67	63	71	66	63	70	66	63	62
9	79	70	64	60	78	69	64	60	68	63	60	67	63	60	67	63	60	58
10	75	66	61	57	74	66	61	57	65	60	57	64	60	57	64	60	57	55

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	521621
5°	499872
10°	440776
15°	371466
20°	304995
25°	247202
30°	183008
35°	110158
40°	49057
45°	19075
50°	6841
55°	1995
60°	1406
65°	1051
70°	108
75°	572
80°	0
85°	1698



TEST NUMBER: P246988

CATALOG NUMBER: LSR8B100D010 EC8B100950 8LBM0LI

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	1474.3	14.3
10°-20°	3231.9	31.4
20°-30°	3296.0	32.0
30°-40°	1846.0	17.9
40°-50°	393.7	3.8
50°-60°	48.8	0.5
60°-70°	12.7	0.1
70°-80°	3.0	0.0
80°-90°	1.6	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	8002.2	77.6
0°-40°	9848.2	95.5
0°-60°	10290.7	99.8
0°-90°	10308.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	10308.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	16916	
5°	16149	###
15°	11636	3232
25°	7266	3296
35°	2926	1846
45°	437	394
55°	37	49
65°	14	13
75°	5	3
85°	5	2
90°	0	



TEST NUMBER: P246988

CATALOG NUMBER: LSR8B100D010 EC8B100950 8LBM0LI

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	16915.8
2.5°	16725.2
5°	16148.8
7.5°	15221.3
10°	14076.9
12.5°	12848.6
15°	11635.9
17.5°	10416.0
20°	9294.3
22.5°	8250.6
25°	7265.5
27.5°	6231.4
30°	5139.7
32.5°	3998.9
35°	2926.3
37.5°	1960.5
40°	1218.7
42.5°	728.6
45°	437.4
47.5°	243.3
50°	142.6
52.5°	75.5
55°	37.1
57.5°	26.4
60°	22.8
62.5°	10.8
65°	14.4
67.5°	14.4
70°	1.2
72.5°	3.6
75°	4.8
77.5°	2.4
80°	0.0
82.5°	1.2
85°	4.8
87.5°	0.0
90°	0.0

(END OF REPORT)