

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P249864

Luminaire Tested: **LSR8B120D010 EC8B120930 8LBN0H**

Issue Date: 03/03/2020

Test Information

Test Method: LM-79-08
Report Number: P249864
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P13959)
Test Lab: INNOVATION CENTER-P1
Issue Date: 03/03/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LSR8B120D010 EC8B120930 8LBN0H
Description: PORTFOLIO 8 INCH NARROW DISTRIBUTION 50 DEGREE CUTOFF RECESSED
DOWNLIGHT- CYLINDEC
97 CRI 3000 CCT WITH SEMI-SPECULAR CLEAR TRIM
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 9169.7 lumens
Efficiency: N/A
Efficacy: 77.5 lumens/watt
Spacing Criteria (0/90/45): 0.77 / 0.77 / 0.81
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 118.3
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P249864

CATALOG NUMBER: LSR8B120D010 EC8B120930 8LBN0H

Luminous Intensity Polar Plot





TEST NUMBER: P249864

CATALOG NUMBER: LSR8B120D010 EC8B120930 8LBN0H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	114	111	109	106	111	109	107	105	105	103	101		101	100	98		98	97	96	94
2	108	103	100	96	106	102	98	95	99	96	93		96	93	91		93	91	89	88
3	103	97	92	88	101	95	91	87	93	89	86		90	87	85		88	85	83	82
4	98	91	85	81	96	89	84	81	87	83	80		85	82	79		83	80	78	76
5	93	85	79	75	92	84	79	75	82	78	74		81	77	74		79	76	73	71
6	89	80	74	70	87	79	74	70	78	73	69		76	72	69		75	71	68	67
7	84	75	70	66	83	75	69	65	74	69	65		72	68	65		71	67	64	63
8	81	71	65	62	79	71	65	61	70	65	61		69	64	61		68	64	61	59
9	77	68	62	58	76	67	62	58	66	61	58		65	61	57		64	60	57	56
10	73	64	58	55	72	64	58	55	63	58	54		62	57	54		61	57	54	53

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P249864

CATALOG NUMBER: LSR8B120D010 EC8B120930 8LBN0H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	1146.9	12.5
10°-20°	2692.5	29.4
20°-30°	2942.8	32.1
30°-40°	1751.2	19.1
40°-50°	480.3	5.2
50°-60°	108.8	1.2
60°-70°	33.6	0.4
70°-80°	10.2	0.1
80°-90°	3.4	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	6782.2	74.0
0°-40°	8533.4	93.1
0°-60°	9122.5	99.5
0°-90°	9169.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	9169.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	12577	
5°	12375	###
15°	9663	2693
25°	6501	2943
35°	2771	1751
45°	562	480
55°	109	109
65°	34	34
75°	9	10
85°	3	3
90°	0	



TEST NUMBER: P249864

CATALOG NUMBER: LSR8B120D010 EC8B120930 8LBN0H

CANDELA DISTRIBUTION (FULL):

	0°
0°	12576.9
1°	12601.7
2°	12586.3
3°	12555.2
4°	12483.9
5°	12375.3
6°	12235.6
7°	12049.4
8°	11832.2
9°	11580.8
10°	11298.4
11°	10997.5
12°	10674.7
13°	10342.7
14°	9998.3
15°	9663.1
16°	9334.2
17°	9011.5
18°	8688.8
19°	8366.0
20°	8052.6
22.5°	7264.4
25°	6501.0
27.5°	5660.0
30°	4726.0
32.5°	3723.7
35°	2771.1
37.5°	1927.0
40°	1278.5
42.5°	837.8
45°	561.6
47.5°	372.4
50°	248.3
52.5°	152.0
55°	108.6
57.5°	77.6
60°	59.0
62.5°	43.5
65°	34.1
67.5°	21.7
70°	15.5
72.5°	12.4
75°	9.3
77.5°	6.2
80°	6.2



TEST NUMBER: P249864

CATALOG NUMBER: LSR8B120D010 EC8B120930 8LBN0H

CANDELA DISTRIBUTION (continued):

	0°
82.5°	3.1
85°	3.1
87.5°	3.1
90°	0.0

(END OF REPORT)