

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P250431

Luminaire Tested: **LSR8B120D010 EC8B120940 8LBN0B**

Issue Date: 03/03/2020

Test Information

Test Method: LM-79-08
Report Number: P250431
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P13948)
Test Lab: INNOVATION CENTER-P1
Issue Date: 03/03/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LSR8B120D010 EC8B120940 8LBN0B
Description: PORTFOLIO 8 INCH NARROW DISTRIBUTION 50 DEGREE CUTOFF RECESSED
DOWNLIGHT- CYLINDEC
90 CRI 4000 CCT WITH SPECULAR BLACK TRIM
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 6485.0 lumens
Efficiency: N/A
Efficacy: 54.8 lumens/watt
Spacing Criteria (0/90/45): 0.69 / 0.69 / 0.77
Luminous Opening: Circular (Dia: 0.67' x H: 0')
CIE Type: Direct


Input Watts (W): 118.3
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P250431

CATALOG NUMBER: LSR8B120D010 EC8B120940 8LBN0B

Luminous Intensity Polar Plot





TEST NUMBER: P250431

CATALOG NUMBER: LSR8B120D010 EC8B120940 8LBN0B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	114	111	109	107	112	109	107	105	105	104	102	101	100	99	98	97	96	94
2	109	104	101	97	107	103	99	96	99	97	94	96	94	92	94	92	90	89
3	104	98	93	90	102	97	92	89	94	90	88	92	89	86	89	87	85	83
4	99	92	87	83	97	91	86	83	89	85	82	87	84	81	85	82	80	78
5	95	87	82	78	93	86	81	77	84	80	77	83	79	76	81	78	75	74
6	90	82	77	73	89	81	76	72	80	75	72	79	75	71	77	74	71	70
7	86	78	72	68	85	77	72	68	76	71	68	75	71	67	74	70	67	66
8	83	74	68	64	81	73	68	64	72	67	64	71	67	64	70	66	63	62
9	79	70	65	61	78	70	64	61	69	64	61	68	63	60	67	63	60	59
10	76	67	61	58	75	66	61	58	65	61	57	65	60	57	64	60	57	56

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	319538
5°	314432
10°	279366
15°	230454
20°	194086
25°	163704
30°	122569
35°	69367
40°	27429
45°	7366
50°	1410
55°	0
60°	204
65°	0
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P250431

CATALOG NUMBER: LSR8B120D010 EC8B120940 8LBN0B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	930.2	14.3
10°-20°	2021.8	31.2
20°-30°	2170.6	33.5
30°-40°	1173.1	18.1
40°-50°	183.0	2.8
50°-60°	5.0	0.1
60°-70°	1.2	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	5122.6	79.0
0°-40°	6295.7	97.1
0°-60°	6483.8	100.0
0°-90°	6485.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6485.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	10362	
5°	10158	930
15°	7219	2022
25°	4811	2171
35°	1843	1173
45°	169	183
55°	0	5
65°	0	1
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P250431

CATALOG NUMBER: LSR8B120D010 EC8B120940 8LBN0B

CANDELA DISTRIBUTION (FULL):

0°	
0°	10362.4
1°	10382.1
2°	10372.3
3°	10336.8
4°	10268.5
5°	10158.0
6°	10005.8
7°	9801.1
8°	9544.9
9°	9250.0
10°	8922.0
11°	8578.0
12°	8221.1
13°	7864.6
14°	7533.3
15°	7218.8
16°	6930.0
17°	6650.9
18°	6391.3
19°	6148.3
20°	5914.5
21°	5687.3
22°	5473.1
23°	5259.3
24°	5035.4
25°	4811.4
26°	4584.2
27°	4324.8
28°	4039.1
29°	3747.5
30°	3442.3
31°	3114.7
32°	2786.8
33°	2462.4
34°	2134.8
35°	1842.7
37.5°	1177.7
40°	681.4
42.5°	363.5
45°	168.9
47.5°	91.0
50°	29.4
52.5°	3.3
55°	0.0
57.5°	3.3



TEST NUMBER: P250431

CATALOG NUMBER: LSR8B120D010 EC8B120940 8LBN0B

CANDELA DISTRIBUTION (continued):

	0°
60°	3.3
62.5°	0.0
65°	0.0
67.5°	3.3
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)