

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P250361

Luminaire Tested: **LSR8B120D010 EC8B1209727 8LBN0GPH**

Issue Date: 03/03/2020

Test Information

Test Method: LM-79-08
Report Number: P250361
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P13948)
Test Lab: INNOVATION CENTER-P1
Issue Date: 03/03/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LSR8B120D010 EC8B1209727 8LBN0GPH
Description: PORTFOLIO 8 INCH NARROW DISTRIBUTION 50 DEGREE CUTOFF RECESSED
DOWNLIGHT- CYLINDEC
97 CRI 2700 CCT WITH GRAPHITE TRIM
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 6959.0 lumens
Efficiency: N/A
Efficacy: 58.8 lumens/watt
Spacing Criteria (0/90/45): 0.69 / 0.69 / 0.77
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 118.3
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P250361

CATALOG NUMBER: LSR8B120D010 EC8B1209727 8LBN0GPH

Luminous Intensity Polar Plot





TEST NUMBER: P250361

CATALOG NUMBER: LSR8B120D010 EC8B1209727 8LBN0GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	114	111	109	107	112	109	107	105	105	104	102		101	100	99		98	97	96	94
2	109	104	101	97	107	103	99	96	99	97	94		96	94	92		94	92	90	89
3	104	98	93	90	102	97	92	89	94	90	88		92	89	86		89	87	85	83
4	99	92	87	83	97	91	86	83	89	85	82		87	84	81		85	82	80	78
5	95	87	82	78	93	86	81	77	84	80	77		83	79	76		81	78	75	74
6	90	82	77	73	89	81	76	72	80	75	72		79	75	71		77	74	71	70
7	86	78	72	68	85	77	72	68	76	71	68		75	71	67		74	70	67	66
8	83	74	68	64	81	73	68	64	72	67	64		71	67	64		70	66	63	62
9	79	70	65	61	78	70	64	61	69	64	61		68	63	60		67	63	60	59
10	76	67	61	58	75	66	61	58	65	61	57		65	60	57		64	60	57	56

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P250361

CATALOG NUMBER: LSR8B120D010 EC8B1209727 8LBN0GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	998.2	14.3
10°-20°	2169.6	31.2
20°-30°	2329.2	33.5
30°-40°	1258.9	18.1
40°-50°	196.4	2.8
50°-60°	5.4	0.1
60°-70°	1.3	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	5497.0	79.0
0°-40°	6755.9	97.1
0°-60°	6957.7	100.0
0°-90°	6959.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6959.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	11120	
5°	10900	998
15°	7746	2170
25°	5163	2329
35°	1977	1259
45°	181	196
55°	0	5
65°	0	1
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P250361

CATALOG NUMBER: LSR8B120D010 EC8B1209727 8LBN0GPH

CANDELA DISTRIBUTION (FULL):

	0°
0°	11119.8
1°	11140.9
2°	11130.4
3°	11092.3
4°	11019.1
5°	10900.5
6°	10737.2
7°	10517.5
8°	10242.5
9°	9926.1
10°	9574.1
11°	9205.0
12°	8822.0
13°	8439.4
14°	8084.0
15°	7746.4
16°	7436.5
17°	7137.0
18°	6858.5
19°	6597.7
20°	6346.8
21°	6103.0
22°	5873.1
23°	5643.7
24°	5403.4
25°	5163.0
26°	4919.2
27°	4640.9
28°	4334.3
29°	4021.4
30°	3694.0
31°	3342.4
32°	2990.4
33°	2642.4
34°	2290.8
35°	1977.4
37.5°	1263.8
40°	731.2
42.5°	390.1
45°	181.2
47.5°	97.7
50°	31.6
52.5°	3.5
55°	0.0
57.5°	3.5



TEST NUMBER: P250361

CATALOG NUMBER: LSR8B120D010 EC8B1209727 8LBN0GPH

CANDELA DISTRIBUTION (continued):

	0°
60°	3.5
62.5°	0.0
65°	0.0
67.5°	3.5
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)