

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P250446

Luminaire Tested: **LSR8B150D010 EC8B150927 8LBN0B**

Issue Date: 03/03/2020

Test Information

Test Method: LM-79-08
Report Number: P250446
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P13948)
Test Lab: INNOVATION CENTER-P1
Issue Date: 03/03/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LSR8B150D010 EC8B150927 8LBN0B
Description: PORTFOLIO 8 INCH NARROW DISTRIBUTION 50 DEGREE CUTOFF RECESSED
DOWNLIGHT- CYLINDEC
97 CRI 2700 CCT WITH SPECULAR BLACK TRIM
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 7240.5 lumens
Efficiency: N/A
Efficacy: 45.7 lumens/watt
Spacing Criteria (0/90/45): 0.69 / 0.69 / 0.77
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 158.5
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P250446

CATALOG NUMBER: LSR8B150D010 EC8B150927 8LBN0B

Luminous Intensity Polar Plot





TEST NUMBER: P250446

CATALOG NUMBER: LSR8B150D010 EC8B150927 8LBN0B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	114	111	109	107	112	109	107	105	105	104	102		101	100	99		98	97	96	94
2	109	104	101	97	107	103	99	96	99	97	94		96	94	92		94	92	90	89
3	104	98	93	90	102	97	92	89	94	90	88		92	89	86		89	87	85	83
4	99	92	87	83	97	91	86	83	89	85	82		87	84	81		85	82	80	78
5	95	87	82	78	93	86	81	77	84	80	77		83	79	76		81	78	75	74
6	90	82	77	73	89	81	76	72	80	75	72		79	75	71		77	74	71	70
7	86	78	72	68	85	77	72	68	76	71	68		75	71	67		74	70	67	66
8	83	74	68	64	81	73	68	64	72	67	64		71	67	64		70	66	63	62
9	79	70	65	61	78	70	64	61	69	64	61		68	63	60		67	63	60	59
10	76	67	61	58	75	66	61	58	65	61	57		65	60	57		64	60	57	56

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P250446

CATALOG NUMBER: LSR8B150D010 EC8B150927 8LBN0B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	1038.6	14.3
10°-20°	2257.3	31.2
20°-30°	2423.4	33.5
30°-40°	1309.8	18.1
40°-50°	204.3	2.8
50°-60°	5.6	0.1
60°-70°	1.4	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	5719.4	79.0
0°-40°	7029.2	97.1
0°-60°	7239.1	100.0
0°-90°	7240.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	7240.5	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	11570	
5°	11342	###
15°	8060	2257
25°	5372	2423
35°	2057	1310
45°	188	204
55°	0	6
65°	0	1
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P250446

CATALOG NUMBER: LSR8B150D010 EC8B150927 8LBN0B

CANDELA DISTRIBUTION (FULL):

	0°
0°	11569.6
1°	11591.6
2°	11580.6
3°	11541.0
4°	11464.9
5°	11341.5
6°	11171.5
7°	10943.0
8°	10656.9
9°	10327.6
10°	9961.4
11°	9577.4
12°	9178.9
13°	8780.8
14°	8410.9
15°	8059.7
16°	7737.3
17°	7425.8
18°	7136.0
19°	6864.6
20°	6603.5
21°	6350.0
22°	6110.7
23°	5871.9
24°	5622.0
25°	5371.9
26°	5118.2
27°	4828.6
28°	4509.7
29°	4184.1
30°	3843.3
31°	3477.6
32°	3111.4
33°	2749.3
34°	2383.5
35°	2057.4
37.5°	1314.9
40°	760.7
42.5°	405.8
45°	188.5
47.5°	101.6
50°	32.8
52.5°	3.7
55°	0.0
57.5°	3.7



TEST NUMBER: P250446

CATALOG NUMBER: LSR8B150D010 EC8B150927 8LBN0B

CANDELA DISTRIBUTION (continued):

	0°
60°	3.7
62.5°	0.0
65°	0.0
67.5°	3.7
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)