

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P245313

Luminaire Tested: **LSR8B30D010 EC8B30827 8LBS0WH**

Issue Date: 03/03/2020

**Test Information**

Test Method: LM-79-08  
Report Number: P245313  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-1801-521-15)  
Test Lab: INNOVATION CENTER(G1)  
Issue Date: 03/03/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: PORTFOLIO  
Catalog Number: LSR8B30D010 EC8B30827 8LBS0WH  
Description: PORTFOLIO 8 INCH WIDE SHALLOW DISTRIBUTION 75 DEGREE CUTOFF RECESSED  
DOWNLIGHT- CYLINDEC  
80 CRI 2700 CCT WITH WHEAT TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 3241.0 lumens  
Efficiency: N/A  
Efficacy: 119.6 lumens/watt  
Spacing Criteria (0/90/45): 1.27 / 1.27 / 1.23  
Luminous Opening: Circular (Dia: 0.67' x H: 0')  
CIE Type: Direct


Input Watts (W): 27.1  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P245313

CATALOG NUMBER: LSR8B30D010 EC8B30827 8LBS0WH

### Luminous Intensity Polar Plot





TEST NUMBER: P245313

CATALOG NUMBER: LSR8B30D010 EC8B30827 8LBS0WH

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	112	109	106	104	110	107	104	102	103	101	99		99	97	96		96	94	93	91
2	105	100	95	91	103	98	93	90	94	91	88		91	88	86		89	86	84	82
3	99	91	85	80	96	89	84	79	87	82	78		84	80	77		82	78	76	74
4	92	83	76	71	90	82	76	71	79	74	70		77	73	69		75	71	68	66
5	86	76	69	64	84	75	68	63	73	67	63		71	66	62		70	65	62	60
6	80	70	63	57	79	69	62	57	67	61	57		66	60	56		64	60	56	54
7	75	64	57	52	74	63	57	52	62	56	51		61	55	51		60	55	51	49
8	71	59	52	47	69	59	52	47	57	51	47		56	51	47		55	50	46	45
9	66	55	48	43	65	54	48	43	53	47	43		52	47	43		51	46	43	41
10	63	51	44	40	61	51	44	40	50	44	39		49	43	39		48	43	39	38

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	56606
5°	56822
10°	57539
15°	58664
20°	59501
25°	59746
30°	57918
35°	52860
40°	45728
45°	35999
50°	23219
55°	11397
60°	4687
65°	2050
70°	595
75°	226
80°	160
85°	0



TEST NUMBER: P245313

CATALOG NUMBER: LSR8B30D010 EC8B30827 8LBS0WH

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	175.3	5.4
10°-20°	519.3	16.0
20°-30°	804.0	24.8
30°-40°	871.0	26.9
40°-50°	626.8	19.3
50°-60°	209.7	6.5
60°-70°	31.7	1.0
70°-80°	2.7	0.1
80°-90°	0.4	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1498.7	46.2
0°-40°	2369.7	73.1
0°-60°	3206.2	98.9
0°-90°	3241.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3241.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	1836	
5°	1836	175
15°	1838	519
25°	1756	804
35°	1404	871
45°	826	627
55°	212	210
65°	28	32
75°	2	3
85°	0	0
90°	0	



TEST NUMBER: P245313

CATALOG NUMBER: LSR8B30D010 EC8B30827 8LBS0WH

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	1835.7
2.5°	1835.7
5°	1835.7
7.5°	1836.7
10°	1837.6
12.5°	1839.5
15°	1837.6
17.5°	1830.1
20°	1813.2
22.5°	1787.9
25°	1756.0
27.5°	1705.4
30°	1626.6
32.5°	1523.4
35°	1404.2
37.5°	1275.7
40°	1136.0
42.5°	985.9
45°	825.5
47.5°	651.9
50°	484.0
52.5°	332.1
55°	212.0
57.5°	126.6
60°	76.0
62.5°	46.0
65°	28.1
67.5°	14.1
70°	6.6
72.5°	2.8
75°	1.9
77.5°	1.9
80°	0.9
82.5°	0.9
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)