

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P243957

Luminaire Tested: **LSR8B30D010 EC8B30835 8LBM0LI**

Issue Date: 03/03/2020

Test Information

Test Method: LM-79-08
Report Number: P243957
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-1801-521-11)
Test Lab: INNOVATION CENTER(G1)
Issue Date: 03/03/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LSR8B30D010 EC8B30835 8LBM0LI
Description: PORTFOLIO 8 INCH MEDIUM DISTRIBUTION 55 DEG CUTOFF RECESSED
DOWNLIGHT- CYLINDEC
80 CRI 3500 CCT WITH SPECULAR CLEAR TRIM
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3209.0 lumens
Efficiency: N/A
Efficacy: 118.4 lumens/watt
Spacing Criteria (0/90/45): 0.63 / 0.63 / 0.72
Luminous Opening: Circular (Dia: 0.67' x H: 0')
CIE Type: Direct


Input Watts (W): 27.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P243957

CATALOG NUMBER: LSR8B30D010 EC8B30835 8LBM0LI

Luminous Intensity Polar Plot





TEST NUMBER: P243957

CATALOG NUMBER: LSR8B30D010 EC8B30835 8LBM0LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

| | | | | | | | | | | | | | | | | | | |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| RF | 20 | | | | 20 | | | | 20 | | | | 20 | | | | 20 | |
| RC | 80 | | | | 70 | | | | 50 | | | | 30 | | | | 10 | 0 |
| RW | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 0 |
| RCR | | | | | | | | | | | | | | | | | | |
| 0 | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 | 106 | 106 | 106 | 102 | 102 | 102 | 100 |
| 1 | 114 | 111 | 109 | 107 | 111 | 109 | 107 | 105 | 105 | 104 | 102 | 101 | 100 | 99 | 98 | 97 | 96 | 94 |
| 2 | 109 | 104 | 101 | 97 | 107 | 103 | 99 | 96 | 99 | 97 | 94 | 96 | 94 | 92 | 94 | 92 | 90 | 89 |
| 3 | 104 | 98 | 93 | 90 | 102 | 97 | 92 | 89 | 94 | 90 | 88 | 92 | 89 | 86 | 89 | 87 | 85 | 83 |
| 4 | 99 | 92 | 87 | 83 | 97 | 91 | 86 | 83 | 89 | 85 | 82 | 87 | 84 | 81 | 85 | 82 | 80 | 78 |
| 5 | 95 | 87 | 82 | 78 | 93 | 86 | 81 | 77 | 84 | 80 | 77 | 83 | 79 | 76 | 81 | 78 | 75 | 74 |
| 6 | 90 | 82 | 77 | 73 | 89 | 81 | 76 | 73 | 80 | 75 | 72 | 79 | 75 | 72 | 77 | 74 | 71 | 70 |
| 7 | 86 | 78 | 72 | 69 | 85 | 77 | 72 | 68 | 76 | 71 | 68 | 75 | 71 | 68 | 74 | 70 | 67 | 66 |
| 8 | 83 | 74 | 68 | 65 | 82 | 73 | 68 | 65 | 72 | 68 | 64 | 71 | 67 | 64 | 70 | 67 | 64 | 62 |
| 9 | 79 | 70 | 65 | 61 | 78 | 70 | 65 | 61 | 69 | 64 | 61 | 68 | 64 | 61 | 67 | 63 | 60 | 59 |
| 10 | 76 | 67 | 62 | 58 | 75 | 67 | 61 | 58 | 66 | 61 | 58 | 65 | 61 | 58 | 64 | 60 | 58 | 56 |

AVERAGE LUMINANCE (cd/sqm):

| | |
|-----|--------|
| | 0° |
| 0° | 172625 |
| 5° | 165202 |
| 10° | 147073 |
| 15° | 118151 |
| 20° | 92539 |
| 25° | 74717 |
| 30° | 57897 |
| 35° | 32976 |
| 40° | 12438 |
| 45° | 5364 |
| 50° | 2159 |
| 55° | 806 |
| 60° | 432 |
| 65° | 292 |
| 70° | 180 |
| 75° | 119 |
| 80° | 0 |
| 85° | 0 |



TEST NUMBER: P243957

CATALOG NUMBER: LSR8B30D010 EC8B30835 8LBM0LI

ZONAL LUMENS:

| Zone | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10° | 489.9 | 15.3 |
| 10°-20° | 1027.7 | 32.0 |
| 20°-30° | 1005.7 | 31.3 |
| 30°-40° | 556.4 | 17.3 |
| 40°-50° | 107.7 | 3.4 |
| 50°-60° | 16.5 | 0.5 |
| 60°-70° | 4.1 | 0.1 |
| 70°-80° | 1.1 | 0.0 |
| 80°-90° | 0.0 | 0.0 |
| 90°-100° | 0.0 | 0.0 |
| 100°-110° | 0.0 | 0.0 |
| 110°-120° | 0.0 | 0.0 |
| 120°-130° | 0.0 | 0.0 |
| 130°-140° | 0.0 | 0.0 |
| 140°-150° | 0.0 | 0.0 |
| 150°-160° | 0.0 | 0.0 |
| 160°-170° | 0.0 | 0.0 |
| 170°-180° | 0.0 | 0.0 |
| 0°-30° | 2523.2 | 78.6 |
| 0°-40° | 3079.6 | 96.0 |
| 0°-60° | 3203.9 | 99.8 |
| 0°-90° | 3209.0 | 100.0 |
| 90°-120° | 0.0 | 0.0 |
| 90°-150° | 0.0 | 0.0 |
| 90°-180° | 0.0 | 0.0 |
| 0°-180° | 3209.0 | 100.0 |

CANDELA DISTRIBUTION:

| | 0° | Flux |
|-----|------|------|
| 0° | 5598 | |
| 5° | 5337 | 490 |
| 15° | 3701 | 1028 |
| 25° | 2196 | 1006 |
| 35° | 876 | 556 |
| 45° | 123 | 108 |
| 55° | 15 | 17 |
| 65° | 4 | 4 |
| 75° | 1 | 1 |
| 85° | 0 | 0 |
| 90° | 0 | |



TEST NUMBER: P243957

CATALOG NUMBER: LSR8B30D010 EC8B30835 8LBM0LI

CANDELA DISTRIBUTION (FULL):

| | 0° |
|-------|--------|
| 0° | 5598.1 |
| 2.5° | 5521.1 |
| 5° | 5337.0 |
| 7.5° | 5079.0 |
| 10° | 4697.0 |
| 12.5° | 4214.0 |
| 15° | 3701.0 |
| 17.5° | 3220.0 |
| 20° | 2820.0 |
| 22.5° | 2489.0 |
| 25° | 2196.0 |
| 27.5° | 1920.0 |
| 30° | 1626.0 |
| 32.5° | 1281.0 |
| 35° | 876.0 |
| 37.5° | 527.0 |
| 40° | 309.0 |
| 42.5° | 193.0 |
| 45° | 123.0 |
| 47.5° | 77.0 |
| 50° | 45.0 |
| 52.5° | 25.0 |
| 55° | 15.0 |
| 57.5° | 9.0 |
| 60° | 7.0 |
| 62.5° | 5.0 |
| 65° | 4.0 |
| 67.5° | 3.0 |
| 70° | 2.0 |
| 72.5° | 1.0 |
| 75° | 1.0 |
| 77.5° | 1.0 |
| 80° | 0.0 |
| 82.5° | 0.0 |
| 85° | 0.0 |
| 87.5° | 0.0 |
| 90° | 0.0 |

(END OF REPORT)