

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P246658

Luminaire Tested: **LSR8B40D010 EC8B40940 8LBN0MW**

Issue Date: 03/03/2020

Test Information

Test Method: LM-79-08
Report Number: P246658
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P201839)
Test Lab: INNOVATION CENTER-P1
Issue Date: 03/03/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LSR8B40D010 EC8B40940 8LBN0MW
Description: PORTFOLIO 8 INCH NARROW DISTRIBUTION 50 DEGREE CUTOFF RECESSED
DOWNLIGHT- CYLINDEC
90 CRI 4000 CCT WITH MATTE WHITE TRIM
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3609.0 lumens
Efficiency: N/A
Efficacy: 88.2 lumens/watt
Spacing Criteria (0/90/45): 0.79 / 0.79 / 0.85
Luminous Opening: Circular (Dia: 0.67' x H: 0')
CIE Type: Direct


Input Watts (W): 40.9
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P246658

CATALOG NUMBER: LSR8B40D010 EC8B40940 8LBN0MW

Luminous Intensity Polar Plot





TEST NUMBER: P246658

CATALOG NUMBER: LSR8B40D010 EC8B40940 8LBN0MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	112	109	106	103	109	106	104	101	102	100	98		98	97	95		95	94	92	90
2	105	99	94	90	103	97	93	89	94	90	87		91	88	85		88	86	83	82
3	99	91	85	80	96	89	84	79	87	82	78		84	80	77		82	78	76	74
4	93	84	77	72	91	83	76	72	80	75	71		78	74	70		76	72	69	67
5	87	78	71	66	85	77	70	65	75	69	65		73	68	64		71	67	64	62
6	82	72	65	60	81	71	65	60	70	64	60		68	63	59		67	62	59	57
7	78	67	60	56	76	67	60	55	65	59	55		64	59	55		63	58	54	53
8	74	63	56	52	72	62	56	51	61	55	51		60	55	51		59	54	51	49
9	70	59	53	48	69	59	52	48	58	52	48		57	51	48		56	51	47	46
10	66	56	49	45	65	55	49	45	54	49	45		54	48	45		53	48	45	43

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	116706
5°	115870
10°	105590
15°	90505
20°	80210
25°	71577
30°	57804
35°	40106
40°	25449
45°	18905
50°	16133
55°	14145
60°	12655
65°	11310
70°	9746
75°	8960
80°	8346
85°	7359



TEST NUMBER: P246658

CATALOG NUMBER: LSR8B40D010 EC8B40940 8LBN0MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	345.3	9.6
10°-20°	798.6	22.1
20°-30°	949.7	26.3
30°-40°	671.4	18.6
40°-50°	346.5	9.6
50°-60°	237.6	6.6
60°-70°	154.2	4.3
70°-80°	80.9	2.2
80°-90°	24.8	0.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2093.6	58.0
0°-40°	2764.9	76.6
0°-60°	3349.0	92.8
0°-90°	3609.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3609.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3785	
5°	3743	345
15°	2835	799
25°	2104	950
35°	1065	671
45°	434	347
55°	263	238
65°	155	154
75°	75	81
85°	21	23
90°	0	2
95°	0	0
105°	0	0
115°	0	0
125°	0	0
135°	0	0
145°	0	0
155°	0	0
165°	0	0
175°	0	0
180°	0	0



TEST NUMBER: P246658

CATALOG NUMBER: LSR8B40D010 EC8B40940 8LBN0MW

CANDELA DISTRIBUTION (FULL):

0°	
0°	3784.7
2.5°	3784.7
5°	3743.3
7.5°	3605.7
10°	3372.2
12.5°	3093.7
15°	2835.0
17.5°	2622.2
20°	2444.3
22.5°	2276.1
25°	2103.7
27.5°	1887.4
30°	1623.4
32.5°	1339.5
35°	1065.4
37.5°	820.9
40°	632.2
42.5°	508.7
45°	433.5
47.5°	378.8
50°	336.3
52.5°	299.1
55°	263.1
57.5°	231.4
60°	205.2
62.5°	177.9
65°	155.0
67.5°	134.3
70°	108.1
72.5°	92.9
75°	75.2
77.5°	61.1
80°	47.0
82.5°	35.0
85°	20.8
87.5°	12.0
90°	0.0
92.5°	0.0
95°	0.0
97.5°	0.0
100°	0.0
102.5°	0.0
105°	0.0
107.5°	0.0
110°	0.0



TEST NUMBER: P246658

CATALOG NUMBER: LSR8B40D010 EC8B40940 8LBN0MW

CANDELA DISTRIBUTION (continued):

	0°
112.5°	0.0
115°	0.0
117.5°	0.0
120°	0.0
122.5°	0.0
125°	0.0
127.5°	0.0
130°	0.0
132.5°	0.0
135°	0.0
137.5°	0.0
140°	0.0
142.5°	0.0
145°	0.0
147.5°	0.0
150°	0.0
152.5°	0.0
155°	0.0
157.5°	0.0
160°	0.0
162.5°	0.0
165°	0.0
167.5°	0.0
170°	0.0
172.5°	0.0
175°	0.0
177.5°	0.0
180°	0.0

(END OF REPORT)