

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P246275

Luminaire Tested: **LSR8B50D010 EC8B50850 8LBW0B**

Issue Date: 03/03/2020

Test Information

Test Method: LM-79-08
Report Number: P246275
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-1801-521-47)
Test Lab: INNOVATION CENTER(G1)
Issue Date: 03/03/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LSR8B50D010 EC8B50850 8LBW0B
Description: PORTFOLIO 8 INCH WIDE DISTRIBUTION 60 DEGREE CUTOFF RECESSED
DOWNLIGHT- CYLINDEC
80 CRI 5000 CCT WITH SPECULAR BLACK TRIM
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3550.0 lumens
Efficiency: N/A
Efficacy: 67.0 lumens/watt
Spacing Criteria (0/90/45): 1.08 / 1.08 / 1.02
Luminous Opening: Circular (Dia: 0.67' x H: 0')
CIE Type: Direct


Input Watts (W): 53
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P246275

CATALOG NUMBER: LSR8B50D010 EC8B50850 8LBW0B

Luminous Intensity Polar Plot





TEST NUMBER: P246275

CATALOG NUMBER: LSR8B50D010 EC8B50850 8LBW0B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10				
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	111	106	106	106	106	102	102	102	102	100
1	113	110	108	106	111	108	106	104	104	102	101	101	101	99	98	98	97	96	95	95	93
2	107	102	98	95	105	101	97	94	97	94	92	92	94	92	90	90	92	90	88	88	86
3	102	95	90	86	100	94	89	85	91	87	84	84	89	85	82	82	86	84	81	81	80
4	96	88	83	78	94	87	82	78	85	80	77	77	83	79	76	76	81	78	75	75	74
5	91	82	76	72	89	81	76	71	80	75	71	71	78	74	70	70	76	73	70	70	68
6	86	77	71	66	85	76	70	66	74	69	65	65	73	68	65	65	72	68	65	65	63
7	82	72	66	61	80	71	65	61	70	64	61	61	69	64	60	60	67	63	60	60	58
8	77	67	61	57	76	67	61	57	66	60	56	56	65	60	56	56	64	59	56	56	54
9	73	63	57	53	72	63	57	53	62	56	52	52	61	56	52	52	60	55	52	52	51
10	70	59	53	49	68	59	53	49	58	53	49	49	57	52	49	49	57	52	49	49	47

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	100104
5°	97586
10°	94988
15°	93222
20°	90793
25°	87578
30°	80354
35°	61612
40°	29313
45°	11164
50°	5450
55°	2231
60°	555
65°	131
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P246275

CATALOG NUMBER: LSR8B50D010 EC8B50850 8LBW0B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	297.2	8.4
10°-20°	821.7	23.1
20°-30°	1173.3	33.1
30°-40°	972.4	27.4
40°-50°	239.8	6.8
50°-60°	43.2	1.2
60°-70°	2.4	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2292.2	64.6
0°-40°	3264.6	92.0
0°-60°	3547.6	99.9
0°-90°	3550.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3550.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3246	
5°	3153	297
15°	2920	822
25°	2574	1173
35°	1637	972
45°	256	240
55°	42	43
65°	2	2
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P246275

CATALOG NUMBER: LSR8B50D010 EC8B50850 8LBW0B

CANDELA DISTRIBUTION (FULL):

0°	
0°	3246.3
2.5°	3219.3
5°	3152.6
7.5°	3087.7
10°	3033.6
12.5°	2981.3
15°	2920.1
17.5°	2848.0
20°	2766.8
22.5°	2674.9
25°	2574.0
27.5°	2437.0
30°	2256.7
32.5°	2002.6
35°	1636.7
37.5°	1182.4
40°	728.2
42.5°	423.6
45°	256.0
47.5°	169.4
50°	113.6
52.5°	73.9
55°	41.5
57.5°	19.8
60°	9.0
62.5°	3.6
65°	1.8
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)