

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P250568

Luminaire Tested: **LSR8B80D010 EC8B80850 8LBM0B**

Issue Date: 03/03/2020

Test Information

Test Method: LM-79-08
Report Number: P250568
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P13928)
Test Lab: INNOVATION CENTER-P1
Issue Date: 03/03/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LSR8B80D010 EC8B80850 8LBM0B
Description: PORTFOLIO 8 INCH MEDIUM DISTRIBUTION 55 DEG CUTOFF RECESSED
DOWNLIGHT- CYLINDEC
80 CRI 5000 CCT WITH SPECULAR BLACK TRIM
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 5405.0 lumens
Efficiency: N/A
Efficacy: 72.6 lumens/watt
Spacing Criteria (0/90/45): 0.79 / 0.79 / 0.87
Luminous Opening: Circular (Dia: 0.67' x H: 0')
CIE Type: Direct


Input Watts (W): 74.4
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P250568

CATALOG NUMBER: LSR8B80D010 EC8B80850 8LBM0B

Luminous Intensity Polar Plot





TEST NUMBER: P250568

CATALOG NUMBER: LSR8B80D010 EC8B80850 8LBM0B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	114	111	108	106	111	109	107	105	105	103	101		101	100	98		98	97	96	94
2	108	103	99	96	106	102	98	95	98	95	93		95	93	91		93	91	89	87
3	103	96	92	88	101	95	91	87	92	89	86		90	87	84		88	85	83	81
4	98	90	85	81	96	89	84	80	87	83	79		85	81	78		83	80	77	76
5	93	85	79	75	91	84	78	74	82	77	74		80	76	73		79	75	72	71
6	88	79	74	69	87	79	73	69	77	72	69		76	71	68		74	71	68	66
7	84	75	69	65	83	74	68	64	73	68	64		72	67	64		70	66	63	62
8	80	70	64	60	79	70	64	60	69	64	60		68	63	60		67	63	60	58
9	76	66	61	57	75	66	60	57	65	60	56		64	60	56		63	59	56	55
10	72	63	57	53	71	62	57	53	62	57	53		61	56	53		60	56	53	51

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	216261
5°	209649
10°	183611
15°	162101
20°	148539
25°	136774
30°	113838
35°	75612
40°	36800
45°	13327
50°	4011
55°	280
60°	0
65°	190
70°	0
75°	0
80°	462
85°	0



TEST NUMBER: P250568

CATALOG NUMBER: LSR8B80D010 EC8B80850 8LBM0B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	616.0	11.4
10°-20°	1430.6	26.5
20°-30°	1814.9	33.6
30°-40°	1243.3	23.0
40°-50°	283.4	5.2
50°-60°	14.1	0.3
60°-70°	0.6	0.0
70°-80°	1.0	0.0
80°-90°	1.1	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3861.5	71.4
0°-40°	5104.8	94.4
0°-60°	5402.3	99.9
0°-90°	5405.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5405.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	7013	
5°	6773	616
15°	5078	1431
25°	4020	1815
35°	2009	1243
45°	306	283
55°	5	14
65°	3	1
75°	0	1
85°	0	1
90°	0	



TEST NUMBER: P250568

CATALOG NUMBER: LSR8B80D010 EC8B80850 8LBM0B

CANDELA DISTRIBUTION (FULL):

0°	
0°	7013.2
1°	7049.7
2°	7036.6
3°	6984.4
4°	6895.6
5°	6772.9
6°	6624.0
7°	6451.6
8°	6260.9
9°	6057.1
10°	5863.9
11°	5686.3
12°	5495.6
13°	5357.2
14°	5210.9
15°	5077.7
16°	4957.5
17°	4840.0
18°	4730.3
19°	4623.2
20°	4526.5
21°	4427.3
22°	4325.4
23°	4236.6
24°	4137.4
25°	4019.9
26°	3889.2
27°	3737.8
28°	3575.8
29°	3395.6
30°	3197.1
31°	2972.4
32°	2740.0
33°	2497.1
34°	2248.9
35°	2008.6
37.5°	1418.3
40°	914.2
42.5°	538.1
45°	305.6
47.5°	164.6
50°	83.6
52.5°	15.7
55°	5.2
57.5°	2.6



TEST NUMBER: P250568

CATALOG NUMBER: LSR8B80D010 EC8B80850 8LBM0B

CANDELA DISTRIBUTION (continued):

	0°
60°	0.0
62.5°	0.0
65°	2.6
67.5°	0.0
70°	0.0
72.5°	2.6
75°	0.0
77.5°	0.0
80°	2.6
82.5°	0.0
85°	0.0
87.5°	2.6
90°	0.0

(END OF REPORT)