

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P250611

Luminaire Tested: **LSR8B90D010 EC8B90927 8LBM0B**

Issue Date: 03/03/2020

Test Information

Test Method: LM-79-08
Report Number: P250611
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P13928)
Test Lab: INNOVATION CENTER-P1
Issue Date: 03/03/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LSR8B90D010 EC8B90927 8LBM0B
Description: PORTFOLIO 8 INCH MEDIUM DISTRIBUTION 55 DEG CUTOFF RECESSED
DOWNLIGHT- CYLINDEC
97 CRI 2700 CCT WITH SPECULAR BLACK TRIM
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 4708.0 lumens
Efficiency: N/A
Efficacy: 54.7 lumens/watt
Spacing Criteria (0/90/45): 0.79 / 0.79 / 0.87
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 86.1
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P250611

CATALOG NUMBER: LSR8B90D010 EC8B90927 8LBM0B

Luminous Intensity Polar Plot





TEST NUMBER: P250611

CATALOG NUMBER: LSR8B90D010 EC8B90927 8LBM0B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	114	111	108	106	111	109	107	105	105	103	101		101	100	98		98	97	96	94
2	108	103	99	96	106	102	98	95	98	95	93		95	93	91		93	91	89	87
3	103	96	92	88	101	95	91	87	92	89	86		90	87	84		88	85	83	81
4	98	90	85	81	96	89	84	80	87	83	79		85	81	78		83	80	77	76
5	93	85	79	75	91	84	78	74	82	77	74		80	76	73		79	75	72	71
6	88	79	74	69	87	79	73	69	77	72	69		76	71	68		74	71	68	66
7	84	75	69	65	83	74	68	64	73	68	64		72	67	64		70	66	63	62
8	80	70	64	60	79	70	64	60	69	64	60		68	63	60		67	63	60	58
9	76	66	61	57	75	66	60	57	65	60	56		64	60	56		63	59	56	55
10	72	63	57	53	71	62	57	53	62	57	53		61	56	53		60	56	53	51

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P250611

CATALOG NUMBER: LSR8B90D010 EC8B90927 8LBM0B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	536.6	11.4
10°-20°	1246.1	26.5
20°-30°	1580.9	33.6
30°-40°	1083.0	23.0
40°-50°	246.8	5.2
50°-60°	12.3	0.3
60°-70°	0.5	0.0
70°-80°	0.9	0.0
80°-90°	0.9	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3363.6	71.4
0°-40°	4446.6	94.4
0°-60°	4705.7	100.0
0°-90°	4708.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4708.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	6109	
5°	5900	537
15°	4423	1246
25°	3502	1581
35°	1750	1083
45°	266	247
55°	5	12
65°	2	1
75°	0	1
85°	0	1
90°	0	



TEST NUMBER: P250611

CATALOG NUMBER: LSR8B90D010 EC8B90927 8LBM0B

CANDELA DISTRIBUTION (FULL):

0°	
0°	6109.0
1°	6140.8
2°	6129.3
3°	6083.9
4°	6006.5
5°	5899.6
6°	5769.9
7°	5619.8
8°	5453.7
9°	5276.1
10°	5107.8
11°	4953.2
12°	4787.1
13°	4666.5
14°	4539.0
15°	4423.0
16°	4318.3
17°	4215.9
18°	4120.4
19°	4027.0
20°	3942.9
21°	3856.5
22°	3767.7
23°	3690.4
24°	3603.9
25°	3501.6
26°	3387.8
27°	3255.9
28°	3114.8
29°	2957.7
30°	2784.8
31°	2589.2
32°	2386.7
33°	2175.1
34°	1959.0
35°	1749.6
37.5°	1235.5
40°	796.3
42.5°	468.7
45°	266.2
47.5°	143.3
50°	72.8
52.5°	13.6
55°	4.6
57.5°	2.2



TEST NUMBER: P250611

CATALOG NUMBER: LSR8B90D010 EC8B90927 8LBM0B

CANDELA DISTRIBUTION (continued):

	0°
60°	0.0
62.5°	0.0
65°	2.2
67.5°	0.0
70°	0.0
72.5°	2.2
75°	0.0
77.5°	0.0
80°	2.2
82.5°	0.0
85°	0.0
87.5°	2.2
90°	0.0

(END OF REPORT)