

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P246258

Luminaire Tested: **LD8B10D010 ER8B10835 8LBW0B**

Issue Date: 03/03/2020

Test Information

Test Method: LM-79-08
Report Number: P246258
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-1801-521-47)
Test Lab: INNOVATION CENTER(G1)
Issue Date: 03/03/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD8B10D010 ER8B10835 8LBW0B
Description: PORTFOLIO 8 INCH WIDE DISTRIBUTION 60 DEGREE CUTOFF RECESSED
DOWNLIGHT
80 CRI 3500 CCT WITH SPECULAR BLACK TRIM
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 733.0 lumens
Efficiency: N/A
Efficacy: 71.9 lumens/watt
Spacing Criteria (0/90/45): 1.08 / 1.08 / 1.02
Luminous Opening: Circular (Dia: 0.67' x H: 0')
CIE Type: Direct


Input Watts (W): 10.2
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P246258

CATALOG NUMBER: LD8B10D010 ER8B10835 8LBW0B

Luminous Intensity Polar Plot





TEST NUMBER: P246258

CATALOG NUMBER: LD8B10D010 ER8B10835 8LBW0B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	113	110	108	106	111	108	106	104	104	102	101	101	99	98	97	96	95	93
2	107	102	98	95	105	101	97	94	97	94	92	94	92	90	92	90	88	86
3	102	95	90	86	100	94	89	85	91	87	84	89	85	82	86	84	81	80
4	96	88	83	78	94	87	82	78	85	80	77	83	79	76	81	78	75	74
5	91	82	76	72	89	81	76	71	80	75	71	78	74	70	76	73	70	68
6	86	77	71	66	85	76	70	66	74	69	65	73	68	65	72	68	65	63
7	82	72	66	61	80	71	65	61	70	64	61	69	64	60	67	63	60	58
8	77	67	61	57	76	67	61	57	66	60	56	65	60	56	64	59	56	54
9	73	63	57	53	72	63	57	53	62	56	52	61	56	52	60	55	52	51
10	70	59	53	49	68	59	53	49	58	53	49	57	52	49	57	52	49	47

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	20670
5°	20148
10°	19614
15°	19247
20°	18747
25°	18084
30°	16593
35°	12720
40°	6054
45°	2303
50°	1123
55°	462
60°	117
65°	29
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P246258

CATALOG NUMBER: LD8B10D010 ER8B10835 8LBW0B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	61.4	8.4
10°-20°	169.7	23.1
20°-30°	242.3	33.1
30°-40°	200.8	27.4
40°-50°	49.5	6.8
50°-60°	8.9	1.2
60°-70°	0.5	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	473.3	64.6
0°-40°	674.1	92.0
0°-60°	732.5	99.9
0°-90°	733.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	733.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	670	
5°	651	61
15°	603	170
25°	532	242
35°	338	201
45°	53	50
55°	9	9
65°	0	0
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P246258

CATALOG NUMBER: LD8B10D010 ER8B10835 8LBW0B

CANDELA DISTRIBUTION (FULL):

	0°
0°	670.3
2.5°	664.7
5°	650.9
7.5°	637.5
10°	626.4
12.5°	615.6
15°	602.9
17.5°	588.0
20°	571.3
22.5°	552.3
25°	531.5
27.5°	503.2
30°	466.0
32.5°	413.5
35°	337.9
37.5°	244.1
40°	150.4
42.5°	87.5
45°	52.8
47.5°	35.0
50°	23.4
52.5°	15.3
55°	8.6
57.5°	4.1
60°	1.9
62.5°	0.7
65°	0.4
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)