

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P250290

Luminaire Tested: **LD8B100D010 ER8B100827 8LBN0GPH**

Issue Date: 03/03/2020

Test Information

Test Method: LM-79-08
Report Number: P250290
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P13948)
Test Lab: INNOVATION CENTER-P1
Issue Date: 03/03/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD8B100D010 ER8B100827 8LBN0GPH
Description: PORTFOLIO 8 INCH NARROW DISTRIBUTION 50 DEGREE CUTOFF RECESSED
DOWNLIGHT
80 CRI 2700 CCT WITH GRAPHITE TRIM
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 8271.0 lumens
Efficiency: N/A
Efficacy: 77.8 lumens/watt
Spacing Criteria (0/90/45): 0.69 / 0.69 / 0.77
Luminous Opening: Circular (Dia: 0.67' x H: 0')
CIE Type: Direct


Input Watts (W): 106.3
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P250290

CATALOG NUMBER: LD8B100D010 ER8B100827 8LBN0GPH

Luminous Intensity Polar Plot





TEST NUMBER: P250290

CATALOG NUMBER: LD8B100D010 ER8B100827 8LBN0GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	114	111	109	107	112	109	107	105	105	104	102	101	100	99	98	97	96	94
2	109	104	101	97	107	103	99	96	99	97	94	96	94	92	94	92	90	89
3	104	98	93	90	102	97	92	89	94	90	88	92	89	86	89	87	85	83
4	99	92	87	83	97	91	86	83	89	85	82	87	84	81	85	82	80	78
5	95	87	82	78	93	86	81	77	84	80	77	83	79	76	81	78	75	74
6	90	82	77	73	89	81	76	72	80	75	72	79	75	71	77	74	71	70
7	86	78	72	68	85	77	72	68	76	71	68	75	71	67	74	70	67	66
8	83	74	68	64	81	73	68	64	72	67	64	71	67	64	70	66	63	62
9	79	70	65	61	78	70	64	61	69	64	61	68	63	60	67	63	60	59
10	76	67	61	58	75	66	61	58	65	61	57	65	60	57	64	60	57	56

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	407539
5°	401029
10°	356306
15°	293919
20°	247539
25°	208786
30°	156328
35°	88471
40°	34981
45°	9393
50°	1799
55°	0
60°	259
65°	0
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P250290

CATALOG NUMBER: LD8B100D010 ER8B100827 8LBN0GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	1186.4	14.3
10°-20°	2578.6	31.2
20°-30°	2768.3	33.5
30°-40°	1496.2	18.1
40°-50°	233.4	2.8
50°-60°	6.4	0.1
60°-70°	1.6	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	6533.4	79.0
0°-40°	8029.6	97.1
0°-60°	8269.4	100.0
0°-90°	8271.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	8271.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	13216	
5°	12956	###
15°	9207	2579
25°	6136	2768
35°	2350	1496
45°	215	233
55°	0	6
65°	0	2
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P250290

CATALOG NUMBER: LD8B100D010 ER8B100827 8LBNOGPH

CANDELA DISTRIBUTION (FULL):

0°	
0°	13216.2
1°	13241.3
2°	13228.9
3°	13183.6
4°	13096.6
5°	12955.6
6°	12761.5
7°	12500.4
8°	12173.6
9°	11797.5
10°	11379.2
11°	10940.5
12°	10485.3
13°	10030.6
14°	9608.1
15°	9206.8
16°	8838.5
17°	8482.6
18°	8151.6
19°	7841.6
20°	7543.4
21°	7253.7
22°	6980.4
23°	6707.7
24°	6422.2
25°	6136.4
26°	5846.7
27°	5515.8
28°	5151.5
29°	4779.6
30°	4390.4
31°	3972.5
32°	3554.2
33°	3140.6
34°	2722.7
35°	2350.2
37.5°	1502.0
40°	869.0
42.5°	463.6
45°	215.4
47.5°	116.1
50°	37.5
52.5°	4.2
55°	0.0
57.5°	4.2



TEST NUMBER: P250290

CATALOG NUMBER: LD8B100D010 ER8B100827 8LBNOGPH

CANDELA DISTRIBUTION (continued):

	0°
60°	4.2
62.5°	0.0
65°	0.0
67.5°	4.2
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)