

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P250354

Luminaire Tested: **LD8B120D010 ER8B120950 8LBN0GPH**

Issue Date: 03/03/2020

**Test Information**

Test Method: LM-79-08  
Report Number: P250354  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P13948)  
Test Lab: INNOVATION CENTER-P1  
Issue Date: 03/03/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: PORTFOLIO  
Catalog Number: LD8B120D010 ER8B120950 8LBN0GPH  
Description: PORTFOLIO 8 INCH NARROW DISTRIBUTION 50 DEGREE CUTOFF RECESSED  
DOWNLIGHT  
90 CRI 5000 CCT WITH GRAPHITE TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 9217.0 lumens  
Efficiency: N/A  
Efficacy: 77.9 lumens/watt  
Spacing Criteria (0/90/45): 0.69 / 0.69 / 0.77  
Luminous Opening: Circular (Dia: 0.67' x H: 0')  
CIE Type: Direct


Input Watts (W): 118.3  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P250354

CATALOG NUMBER: LD8B120D010 ER8B120950 8LBN0GPH

### Luminous Intensity Polar Plot





TEST NUMBER: P250354

CATALOG NUMBER: LD8B120D010 ER8B120950 8LBN0GPH

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	114	111	109	107	112	109	107	105	105	104	102	101	100	99	98	97	96	94
2	109	104	101	97	107	103	99	96	99	97	94	96	94	92	94	92	90	89
3	104	98	93	90	102	97	92	89	94	90	88	92	89	86	89	87	85	83
4	99	92	87	83	97	91	86	83	89	85	82	87	84	81	85	82	80	78
5	95	87	82	78	93	86	81	77	84	80	77	83	79	76	81	78	75	74
6	90	82	77	73	89	81	76	72	80	75	72	79	75	71	77	74	71	70
7	86	78	72	68	85	77	72	68	76	71	68	75	71	67	74	70	67	66
8	83	74	68	64	81	73	68	64	72	67	64	71	67	64	70	66	63	62
9	79	70	65	61	78	70	64	61	69	64	61	68	63	60	67	63	60	59
10	76	67	61	58	75	66	61	58	65	61	57	65	60	57	64	60	57	56

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	454154
5°	446897
10°	397058
15°	327538
20°	275852
25°	232667
30°	174206
35°	98590
40°	38982
45°	10466
50°	2005
55°	0
60°	290
65°	0
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P250354

CATALOG NUMBER: LD8B120D010 ER8B120950 8LBNOGPH

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	1322.1	14.3
10°-20°	2873.6	31.2
20°-30°	3085.0	33.5
30°-40°	1667.3	18.1
40°-50°	260.1	2.8
50°-60°	7.1	0.1
60°-70°	1.8	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	7280.6	79.0
0°-40°	8948.0	97.1
0°-60°	9215.3	100.0
0°-90°	9217.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	9217.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	14728	
5°	14437	###
15°	10260	2874
25°	6838	3085
35°	2619	1667
45°	240	260
55°	0	7
65°	0	2
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P250354

CATALOG NUMBER: LD8B120D010 ER8B120950 8LBNOGPH

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	14727.9
1°	14755.8
2°	14741.9
3°	14691.5
4°	14594.5
5°	14437.4
6°	14221.1
7°	13930.2
8°	13566.0
9°	13146.8
10°	12680.7
11°	12191.8
12°	11684.6
13°	11177.8
14°	10707.0
15°	10259.9
16°	9849.4
17°	9452.8
18°	9083.9
19°	8738.5
20°	8406.2
21°	8083.3
22°	7778.7
23°	7474.9
24°	7156.7
25°	6838.3
26°	6515.4
27°	6146.7
28°	5740.7
29°	5326.3
30°	4892.5
31°	4426.9
32°	3960.8
33°	3499.8
34°	3034.1
35°	2619.0
37.5°	1673.8
40°	968.4
42.5°	516.6
45°	240.0
47.5°	129.4
50°	41.8
52.5°	4.7
55°	0.0
57.5°	4.7



TEST NUMBER: P250354

CATALOG NUMBER: LD8B120D010 ER8B120950 8LBNOGPH

**CANDELA DISTRIBUTION (continued):**

	0°
60°	4.7
62.5°	0.0
65°	0.0
67.5°	4.7
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)