

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P246463

Luminaire Tested: **LD8B15D010 ER8B15827 8LBS0B**

Issue Date: 03/03/2020

Test Information

Test Method: LM-79-08
Report Number: P246463
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-1801-521-17)
Test Lab: INNOVATION CENTER(G1)
Issue Date: 03/03/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD8B15D010 ER8B15827 8LBS0B
Description: PORTFOLIO 8 INCH WIDE SHALLOW DISTRIBUTION 75 DEGREE CUTOFF RECESSED
DOWNLIGHT
80 CRI 2700 CCT WITH SPECULAR BLACK TRIM
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1326.0 lumens
Efficiency: N/A
Efficacy: 92.1 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 1.2 / 1.25
Luminous Opening: Circular (Dia: 0.67' x H: 0')
CIE Type: Direct


Input Watts (W): 14.4
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P246463

CATALOG NUMBER: LD8B15D010 ER8B15827 8LBS0B

Luminous Intensity Polar Plot





TEST NUMBER: P246463

CATALOG NUMBER: LD8B15D010 ER8B15827 8LBS0B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	112	109	106	103	110	107	104	102	103	101	99		99	97	96		96	94	93	91
2	105	99	94	90	103	98	93	89	94	90	87		91	88	85		88	86	84	82
3	98	90	84	79	96	89	83	79	86	81	77		84	80	76		81	78	75	73
4	92	82	76	70	90	81	75	70	79	73	69		77	72	68		75	71	67	66
5	86	75	68	63	84	74	68	63	72	66	62		71	65	61		69	64	61	59
6	80	69	62	56	78	68	61	56	67	60	56		65	60	55		64	59	55	53
7	75	63	56	51	73	63	56	51	61	55	51		60	54	50		59	54	50	48
8	70	59	51	46	69	58	51	46	57	50	46		56	50	46		54	49	46	44
9	66	54	47	42	65	54	47	42	53	46	42		52	46	42		51	45	42	40
10	62	50	43	39	61	50	43	39	49	43	39		48	42	38		47	42	38	37

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	23685
5°	23661
10°	23537
15°	23365
20°	23109
25°	22742
30°	22076
35°	21036
40°	19483
45°	16349
50°	10808
55°	5339
60°	2115
65°	825
70°	126
75°	0
80°	0
85°	0



TEST NUMBER: P246463

CATALOG NUMBER: LD8B15D010 ER8B15827 8LBS0B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	72.5	5.5
10°-20°	206.3	15.6
20°-30°	307.1	23.2
30°-40°	347.8	26.2
40°-50°	281.2	21.2
50°-60°	97.5	7.4
60°-70°	13.3	1.0
70°-80°	0.2	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	585.9	44.2
0°-40°	933.7	70.4
0°-60°	1312.5	99.0
0°-90°	1326.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1326.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	768	
5°	764	73
15°	732	206
25°	668	307
35°	559	348
45°	375	281
55°	99	98
65°	11	13
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P246463

CATALOG NUMBER: LD8B15D010 ER8B15827 8LBS0B

CANDELA DISTRIBUTION (FULL):

0°	
0°	768.1
2.5°	767.2
5°	764.4
7.5°	758.7
10°	751.7
12.5°	742.3
15°	731.9
17.5°	718.8
20°	704.2
22.5°	687.2
25°	668.4
27.5°	645.8
30°	620.0
32.5°	590.8
35°	558.8
37.5°	523.5
40°	484.0
42.5°	435.6
45°	374.9
47.5°	301.5
50°	225.3
52.5°	154.3
55°	99.3
57.5°	58.8
60°	34.3
62.5°	20.2
65°	11.3
67.5°	5.2
70°	1.4
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)